

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

-- --

LOC

DIST

REVISIONS

© COPYRIGHT - By -

ALL RIGHTS RESERVED.

J

-

P

LTR

DESCRIPTION

DATE

DWN

APVD

E4

REVISED

ECR-15-003916

11MAR2015

TS

KB

NOTES;

△ MUST BE KEPT BETWEEN -Z- AND 2mm
 2 THE MATING CAP HSG. PART NUMBER; 175444, 175448
 3 APPLIED CONTACT P/N 173630, 173631
 4 APPLICABLE PRODUCT SPEC NO. 108-5280

注:

△ -Z-面より2mmの範囲で測定
 2. 嵌合相手ハウジング型番: 175444, 175448
 3. 内装するリセパタクルコンタクト型番は173630, 173631
 4. 適用製品規格番号 108-5280

| | | |
|----------|-----------------|------------|
| OBSOLETE | 淡灰 (LIGHT GRAY) | 6-175442-6 |
| | 灰色 (GRAY) | 175442-6 |
| OBSOLETE | 青 (BLUE) | 175442-5 |
| | 白 (WHITE) | 175442-1 |
| | 色 (COLOR) | PART NO |

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN

16JUN2005

M.KADOSAKI

CHK

16JUN05

T.SHINOHARA

APVD

16JUN05

K.BETSUI

PRODUCT SPEC

製品規格

APPLICATION SPEC

取付適用規格

WEIGHT

CUSTOMER DRAWING

NAME
名称

12Pos. PLUG HOUSING
.040/.070 HYBRID I/O CONN. (POWER)
12極 プラグハウジング .040/.070 ハイブリッド I/O コネクタ (パワー用)

SIZE A3 CAGE CODE 00779 DRAWING NO. C=175442 RESTRICTED TO

一般公差
(GENERAL TOLERANCE)

0 < * ≤ 10 : ±0.2
 10 < * ≤ 30 : ±0.25
 30 < * ≤ 100 : ±0.3
 ANGLES : ±3°

DIMENSIONS:
単位: 耗
mm

MATERIAL
材料
PBTTOLERANCES UNLESS
OTHERWISE SPECIFIED:
一般公差

0 PLC ± -
 1 PLC ± -
 2 PLC ± -
 3 PLC ± -
 4 PLC ± -
 ANGLES ± -

FINISH
仕上SCALE
尺度 2:1SHEET
1 of 1REV
E4

1470-19 (3/11)

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[175442-1](#)