

Spezifikation für Freigabe / specification for release

Kunde / customer :

Artikelnummer / part number :

744774010A

LF




Bezeichnung : SPEICHERDROSSEL WE-PD2

description : POWER-CHOKE WE-PD2

DATUM / DATE : 2004-10-11

A Mechanische Abmessungen / dimensions:




marking dot is start winding
& inductance code

	Typ M	
A	5,6 ± 0,2	mm
B	4,5 ± 0,3	mm
C	2,3 ref	mm
D	5,8 ref	mm
E	6,0 ref	mm
F	1,7 ref	mm

B Elektrische Eigenschaften / electrical properties:

Eigenschaften / properties	Testbedingungen / test conditions		Wert / value	Einheit / unit	tol.
Induktivität / inductance	1 kHz	L	1,00	μH	± 20%
Güte Q / Q factor	7,960 MHz	Q	35		
DC-Widerstand / DC-resistance		R _{DC}	0,018	Ω	typ.
Nennstrom / rated current		I _{DC}	5,40	A	max.
Eigenres.-Frequenz / self-res.-frequency		SRF	155,00	MHz	

C Lötpad / soldering spec.:



D Prüfgeräte / test equipment:

HP 4274 A für/for L und/and Q

HP 34401 A für/for R_{DC} und I_{DC}

E Testbedingungen / test conditions:

Luftfeuchtigkeit / humidity: 33%
Umgebungstemperatur / temperature: +20 °C

F Werkstoffe & Zulassungen / material & approvals

Basismaterial / base material: Ferrit
Draht / wire: Class F

G Eigenschaften / general specifications:

Lagertemperatur / storage temperature: -40 °C ~ + 125 °C
Betriebstemp. / operating temperature: -40 °C ~ +125 °C

Freigabe erteilt / general release:	Kunde / customer			
Datum / date	Unterschrift / signature			
	Würth Elektronik	MST	Version 4	06-11-14
		MST	Update	02-03-27
		JH	Neugestaltung	00-12-06
Geprüft / checked	Kontrolliert / approved	Name	Änderung / modification	Datum / date

This electronic component has been designed and developed for usage in general electronic equipment. Before incorporating this component into any equipment where higher safety and reliability is especially required or if there is the possibility of direct damage or injury to human body, for example in the range of aerospace, aviation, nuclear control, submarine, transportation, (automotive control, train control, ship control), transportation signal, disaster prevention, medical, public information network etc. Würth Elektronik eiSos GmbH must be informed before the design-in stage. In addition, sufficient reliability evaluation checks for safety must be performed on every electronic component which is used in electrical circuits that require high safety and reliability functions or performance.

□

Würth Elektronik eiSos GmbH & Co.KG

D-74638 Waldenburg · Max-Eyth-Strasse 1 - 3 · Germany · Telefon (+49) (0) 7942 - 945 - 0 · Telefax (+49) (0) 7942 - 945 - 400
<http://www.we-online.com>

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Wurth Electronics:](#)

[744774010A](#)