

THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.


Material	High Conductivity Seamless Copper Tube
Plating	Electro-Tin
Wire Size	8 STR/FLEX
Wire Type	Stranded Copper: Class B & C, Compact, Class G, H, I, K, M, Locomotive
Wire Strip Length	3/4 in.
Stud Size	1/4 in.
UL Listed Wire Connector	Yes, for applications up to 35kv. Consult cable manufacturer for voltage stress relief instructions with applications greater than 2000 volts.
UL Temperature Rating	90° C
C.S.A Certified Wire Connector	Yes
Panduit Color Code on Barrel	RED
Panduit Die Index No. on Barrel	P21
Alternate Industry Die Index No. () on Barrel	N/A



CERTIFIED



LISTED
Wire Connector



REV	DATE	BY	CHK	RELEASED	ECN	SCALE	DRAWING NO / CAD FILE
00	6/03	SAC	SAC		10850	N/A	LCCX8-14AH-L
				DESCRIPTION			Copper Lug - Two-Hole, Long Flex Barrel with Window, 45° Angle Tongue

PANDUIT CORP. TINLEY PARK, ILLINOIS

LCCX8-14AH-L

Copper Lug - Two-Hole, Long Flex Barrel with Window, 45° Angle Tongue

LCCX8-14AH-CUST

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Panduit:

[LCCX8-14AH-L](#)