

2841.0

H 1,5/14-D BK

H 1,5/14-D BK



Wire-end ferrules, Max. wire cross-section: 1.5 mm², Length: 14 mm, Length of copper pipe: 8 mm, Colour: Black

Business data

|                                            |          |
|--------------------------------------------|----------|
| Product description                        | Ferrules |
| Packaging unit                             | 500      |
| Quantity unit                              | PC       |
| Weight per piece (not including packaging) | 0.12     |
| Weight per piece (including packaging)     | 0.13     |
| Unit of weight                             | G        |
| Customs number                             | 85369010 |
| Country of origin                          | DE       |

**2841.0**

**H 1,5/14-D BK**

**H 1,5/14-D BK**

## Technical Data

---

### Dimensions

|                                  |         |
|----------------------------------|---------|
| Length                           | 14 mm   |
| Length of copper pipe            | 8 mm    |
| Diameter of copper pipe          | 1.7 mm  |
| Diameter plastic collar          | 3.5 mm  |
| Wall thickness of copper pipe    | 0.15 mm |
| Wall thickness of plastic collar | 0.25 mm |

### Connection data

|                              |                     |
|------------------------------|---------------------|
| Wire cross-section, max.     | 1.5 mm <sup>2</sup> |
| Wire cross-section AWG, max. | 16                  |
| Stripping length             | 10 mm               |

### Materials

|                           |                                |
|---------------------------|--------------------------------|
| Copper pipe               | Copper alloy                   |
| Surface                   | Galvanically tin-plated, shiny |
| Plastic collar            | Polypropylene homopolymer      |
| Working temperature, min. | -5 °C                          |
| Working temperature, max. | 105 °C                         |

### Further technical data

|                      |   |
|----------------------|---|
| Insulation available | ✓ |
|----------------------|---|

# Datasheet



2841.0  
H 1,5/14-D BK  
H 1,5/14-D BK

## Approvals

---

## Standards and regulations

---

|                  |   |
|------------------|---|
| DIN 46228-4:1990 | ✓ |
|------------------|---|

---