

**Part Number: 88240**

53 Ohm, RG58, 20 AWG, CMP



## Product Description

RG-58/U type, 20 AWG solid .033" bare copper conductor, plenum, FEP Teflon® insulation, tinned copper braid shield (95% coverage), FEP Teflon® jacket.

## Technical Specifications

### Product Overview

Environmental Space:	Outdoor - Aerial
----------------------	------------------

### Physical Characteristics (Overall)

#### Conductor

AWG	Stranding	Material	Nominal Diameter	No. of Coax
20	Solid	BC - Bare Copper	0.032 in	1

Conductor Count:	1
Conductor Size:	20 AWG

#### Insulation

Material	Material Trade Name	Nominal Diameter
FEP - Fluorinated Ethylene Propylene	Teflon®	0.107 in

#### Outer Shield Material

Type	Material	Coverage [%]
Braid	TC - Tinned Copper	95 %

#### Outer Jacket Material

Material	Material Trade Name	Nominal Diameter
FEP - Fluorinated Ethylene Propylene	Teflon®	0.159 in

### Electrical Characteristics

#### Conductor DCR

Nominal Conductor DCR	Nominal Outer Shield DCR	Outer Conductor DCR
10.2 Ohm/1000ft	6.7 Ohm/1000ft	6.7 Ohm/1000ft

#### Capacitance

Nom. Capacitance Conductor to Shield
26.4 pF/ft

#### Inductance

Nominal Inductance
0.088 µH/ft

#### Impedance

Nominal Characteristic Impedance
53 Ohm

#### High Frequency (Nominal/Typical)

Frequency [MHz]	Nom. Insertion Loss
1 MHz	0.5 dB/100ft
10 MHz	1.2 dB/100ft
50 MHz	3 dB/100ft
100 MHz	4.3 dB/100ft
200 MHz	6.4 dB/100ft
400 MHz	9.7 dB/100ft
700 MHz	13.7 dB/100ft
900 MHz	16.1 dB/100ft
1000 MHz	17.3 dB/100ft

#### Delay

Nominal Delay	Nominal Velocity of Propagation (VP) [%]
1.48 ns/ft	69.5 %

#### Power Rating

Frequency [MHz]	Max. Power Rating [W]	Nominal Power Rating [W]
1 MHz	4,798.7 W	4,798.7 W
10 MHz	1,937.2 W	1,937.2 W
50 MHz	782.4 W	782.4 W
100 MHz	542.2 W	542.2 W
200 MHz	370.3 W	370.3 W
400 MHz	248.5 W	248.5 W
700 MHz	177.7 W	177.7 W
900 MHz	153.0 W	153 W
1,000 MHz	143.2 W	143.2 W

#### Voltage

Non-UL Voltage Rating	UL Voltage Rating
1400 V RMS	300 V RMS

#### Temperature Range

UL Temp Rating:	200°C
Operating Temp Range:	-70°C To +200°C

#### Mechanical Characteristics

Bulk Cable Weight:	24 lbs/1000ft
Max Recommended Pulling Tension:	47 lbs
Min Bend Radius/Minor Axis:	1.5 in

#### Standards

NEC/(UL) Specification:	CMP
CEC/C(UL) Specification:	CMP
RG Type:	58/U Type

#### Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	No
EU RoHS Compliance Date (yyyy-mm-dd):	2005-04-01
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

#### Suitability

Suitability - Aerial:	Yes - When supported by messenger wire
Suitability - Burial:	No
Suitability - Hazardous Locations:	No

Suitability - Indoor:	Yes
Suitability - Outdoor:	Yes
Suitability - Sunlight Resistance:	No

## Flammability, LS0H, Toxicity Testing

UL Flammability:	NFPA 262
CSA Flammability:	FT6
UL voltage rating:	300 V RMS

## Plenum/Non-Plenum

Plenum (Y/N):	Yes
Plenum Number:	8240

## Part Number

### Variants

Item #	Color	Footnote
88240 0101000	Black	C
88240 010500	Black	C

Footnote:	C - CRATE REEL PUT-UP.
-----------	------------------------

© 2018 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.