

[illegible]

PIN-OUT CHART

[illegible][illegible]

LOC	DIST	REVISIONS					
FX	00	REV	LYR	DESCRIPTION	DATE	OWN	APVD
		-	-	SEE SHEET 1	-	-	-

PIN-OUT CHART																																	
		1 / 2																									N	2098376-1	KEY "F"				
		1 / 2																									N	1924686-1	KEY "E"				
		1 / 2																									N	1924685-1	KEY "D"				
		1 / 2																									N	1924684-1	KEY "C"				
		1 / 2																									N	1924683-1	KEY "B"				
		1 / 2																									N	1924682-1	KEY "A"				
5 / 6	3 / 4	1 / 2	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	CPA	ASSEMBLY PART NUMBER	PLUG KEYING OPTION				
SHORTING BAR POSITION			TERMINAL HOLE POSITION																														
CAVITIES W/ A NUMERIC SYMBOL INDICATE SHORTING BAR LOADED			CAVITIES WITH A NUMERIC SYMBOL INDICATE CLOSED TERMINAL HOLE POSITIONS																														
BLANK CAVITIES INDICATE NO SHORTING BAR LOADED			BLANK CAVITIES INDICATE OPEN TERMINAL HOLE POSITIONS																														

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:

mm

MATERIAL

SEE CHART ABOVE

TOLERANCES UNLESS OTHERWISE SPECIFIED:

9 PLC ±.3

1 PLC ±0.10

2 PLC ±.10

3 PLC ±.

4 PLC ±.

ANGLES ±°

FINISH -

DWN R. VESTAL 24JUL2007

CHK W. WELLINSKY 24JUL2007

APVD W. WELLINSKY 24JUL2007

PRODUCT SPEC -

APPLICATION SPEC -

WEIGHT -

CUSTOMER DRAWING

NAME 24 WAY ARM PLUG ASSEMBLY WITH SELECT LOAD SHORTING BARS CUSTOMER SPEC.

SIZE A1

CAGE CODE 00779

DRAWING NO C=1924674

RESTRICTED TO -

SCALE 3:1

SHEET 5

OF 5

REV S

TE Connectivity

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[1-1924675-0](#)