

**Mallory Sonalert Products, Inc.**



Part #:

SC250DR**Sales Outline Drawing**

Revision:

F**Specifications:**

| | |
|-----------------------|--|
| Sound Level Category | Medium |
| Mode of Operation | Continuous |
| Voltage Rating | 60 to 250 VAC/DC |
| Frequency | 2000 \pm 500 Hz |
| Loudness @ 2 FT | 67 to 77 dB(A) Typ. |
| Loudness @ Min V | 60 dB(A) @ 2 Feet and 60 Vac/dc |
| Loudness @ Max V | 72 dB(A) @ 2 Feet and 250 Vac/dc |
| Current Draw | 5-16mA |
| Housing Material | 6/6 Nylon, Color: Black |
| Storage Temperature | -40° to +85° C |
| Operating Temperature | -30° to +65° C |
| Panel Mounting | Recommended hole size is 1.25"(31.75mm). Thread front will fit standard 30mm(1.181") hole. |
| Knurled Nut | Used to attach part to panel. The max recommended torque is 10 in-lbs. |
| Weight (Typical) | 1.6 oz (45g) |
| NEMA 3R,4X, & 12 | Approved with use of ACC03. |
| Options | Please contact factory. |

Dimensions: Inches (mm)**PART DIMENSIONS BEFORE CODE DATE: 0824 5****cUL Recognized****PART DIMENSIONS AFTER CODE DATE: 0825 1****ROHS Compliant**

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Mallory Sonalert:](#)

[SC250DR](#)