



# Optocoupler, Phototriac Output, High dV/dt, Low Input Current



21842-1



i179035\_3



## FEATURES

- High static dV/dt 5 kV/μs
- High input sensitivity 1.6 mA, 2 mA, and 3 mA
- 400 V and 600 V blocking voltage
- 300 mA on-state current
- Isolation test voltage 5300 V<sub>RMS</sub>
- Material categorization:  
For definitions of compliance please see [www.vishay.com/doc?99912](http://www.vishay.com/doc?99912)


**RoHS**  
COMPLIANT

## DESCRIPTION

The VO4254 and VO4256 phototriac consists of a GaAs IRLED optically coupled to a photosensitive non-zero crossing TRIAC packaged in a DIP-6 package.

High input sensitivity is achieved by using an emitter follower phototransistor and a cascaded SCR predriver resulting in an LED trigger current of 1.6 mA for bin D, 2 mA for bin H, and 3 mA for bin M.

The new non zero phototriac family use a proprietary dV/dt clamp resulting in a static dV/dt of greater than 5 kV/μs.

The VO4254 and VO4256 phototriac isolates low-voltage logic from 120 V<sub>AC</sub>, 240 V<sub>AC</sub>, and 380 V<sub>AC</sub> lines to control resistive, inductive, or capacitive loads including motors, solenoids, high current thyristors or TRIAC and relays.



## APPLICATIONS

- Solid-state relays
- Industrial controls
- Office equipment
- Consumer appliances

## AGENCY APPROVALS

- UL1577, file no. E52744 system code H or J, double protection
- cUL - file no. E52744, equivalent to CSA bulletin 5A
- DIN EN 60747-5-5 (VDE 0884) available with option 1
- FIMKO: FI25250

## ORDERING INFORMATION



| AGENCY<br>CERTIFIED/PACKAGE | V <sub>DRM</sub> 400                  |               |               | V <sub>DRM</sub> 600 |               |               |
|-----------------------------|---------------------------------------|---------------|---------------|----------------------|---------------|---------------|
|                             | TRIGGER CURRENT, I <sub>FT</sub> (mA) |               |               |                      |               |               |
|                             | 1.6                                   | 2             | 3             | 1.6                  | 2             | 3             |
| UL, cUL, FIMKO              | 1.6                                   | 2             | 3             | 1.6                  | 2             | 3             |
| DIP-6                       | VO4254D                               | VO4254H       | VO4254M       | VO4256D              | VO4256H       | VO4256M       |
| DIP-6, 400 mil, option 6    | VO4254D-X006                          | VO4254H-X006  | VO4254M-X006  | VO4256D-X006         | VO4256H-X006  | VO4256M-X006  |
| SMD-6, option 7             | VO4254D-X007T                         | VO4254H-X007T | VO4254M-X007T | VO4256D-X007T        | VO4256H-X007T | VO4256M-X007T |
| UL, cUL, FIMKO, VDE         | 1.6                                   | 2             | 3             | 1.6                  | 2             | 3             |
| DIP-6                       | -                                     | -             | -             | VO4256D-X001         | -             | -             |



| ABSOLUTE MAXIMUM RATINGS ( $T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified) |                                                                                |             |            |               |           |
|-------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------|-------------|------------|---------------|-----------|
| PARAMETER                                                                                       | TEST CONDITION                                                                 | PART        | SYMBOL     | VALUE         | UNIT      |
| <b>INPUT</b>                                                                                    |                                                                                |             |            |               |           |
| Reverse voltage                                                                                 |                                                                                |             | $V_R$      | 6             | V         |
| Forward current                                                                                 |                                                                                |             | $I_F$      | 60            | mA        |
| Power dissipation                                                                               |                                                                                |             | $P_{diss}$ | 100           | mW        |
| Derate from 25 °C                                                                               |                                                                                |             |            | 1.33          | mW/°C     |
| <b>OUTPUT</b>                                                                                   |                                                                                |             |            |               |           |
| Peak off-state voltage                                                                          |                                                                                | VO4254D/H/M | $V_{DRM}$  | 400           | V         |
|                                                                                                 |                                                                                | VO4256D/H/M | $V_{DRM}$  | 600           | V         |
| RMS on-state current                                                                            |                                                                                |             | $I_{TM}$   | 300           | mA        |
| Power dissipation                                                                               |                                                                                |             | $P_{diss}$ | 500           | mW        |
| Derate from 25 °C                                                                               |                                                                                |             |            | 6.6           | mW/°C     |
| <b>COUPLER</b>                                                                                  |                                                                                |             |            |               |           |
| Isolation test voltage (between emitter and detector, climate per DIN 500414, part 2, Nov. 74)  | $t = 1\text{ s}$                                                               |             | $V_{ISO}$  | 5300          | $V_{RMS}$ |
| Storage temperature range                                                                       |                                                                                |             | $T_{stg}$  | - 55 to + 150 | °C        |
| Ambient temperature range                                                                       |                                                                                |             | $T_{amb}$  | - 55 to + 100 | °C        |
| Soldering temperature <sup>(2)</sup>                                                            | max. $\leq 10\text{ s}$ dip soldering<br>$\geq 0.5\text{ mm}$ from case bottom |             | $T_{sld}$  | 260           | °C        |

**Notes**

- Stresses in excess of the absolute maximum ratings can cause permanent damage to the device. Functional operation of the device is not implied at these or any other conditions in excess of those given in the operational sections of this document. Exposure to absolute maximum ratings for extended periods of the time can adversely affect reliability.

<sup>(1)</sup> Refer to reflow profile for soldering conditions for surface mounted devices (SMD). Refer to wave profile for soldering conditions for through hole devices (DIP).





Fig. 1 - Recommended Operating Condition

## THERMAL CHARACTERISTICS

| PARAMETER                                                 | SYMBOL         | VALUE | UNIT |
|-----------------------------------------------------------|----------------|-------|------|
| LED power dissipation                                     | $P_{diss}$     | 100   | mW   |
| Output power dissipation                                  | $P_{diss}$     | 500   | mW   |
| Maximum LED junction temperature                          | $T_{jmax.}$    | 125   | °C   |
| Maximum output die junction temperature                   | $T_{jmax.}$    | 125   | °C   |
| Thermal resistance, junction emitter to board             | $\theta_{JEB}$ | 150   | °C/W |
| Thermal resistance, junction emitter to case              | $\theta_{JEC}$ | 139   | °C/W |
| Thermal resistance, junction detector to board            | $\theta_{JDB}$ | 78    | °C/W |
| Thermal resistance, junction detector to case             | $\theta_{JDC}$ | 103   | °C/W |
| Thermal resistance, junction emitter to junction detector | $\theta_{JED}$ | 496   | °C/W |
| Thermal resistance, case to ambient                       | $\theta_{CA}$  | 3563  | °C/W |



### Note

- The thermal characteristics table above were measured at 25 °C and the thermal model is represented in the thermal network below. Each resistance value given in this model can be used to calculate the temperatures at each node for a given operating condition. The thermal resistance from board to ambient will be dependent on the type of PCB, layout and thickness of copper traces. For a detailed explanation of the thermal model, please reference Vishay's Thermal Characteristics of Optocouplers application note.

## ELECTRICAL CHARACTERISTICS ( $T_{amb} = 25\text{ °C}$ , unless otherwise specified)

| PARAMETER                                             | TEST CONDITION                              | PART        | SYMBOL       | MIN. | TYP. | MAX. | UNIT |
|-------------------------------------------------------|---------------------------------------------|-------------|--------------|------|------|------|------|
| <b>INPUT</b>                                          |                                             |             |              |      |      |      |      |
| Forward voltage                                       | $I_F = 10\text{ mA}$                        |             | $V_F$        |      | 1.2  | 1.4  | V    |
| Reverse current                                       | $V_R = 6\text{ V}$                          |             | $I_R$        |      | 0.1  | 10   | μA   |
| Input capacitance                                     | $V_F = 0\text{ V}$ , $f = 1\text{ MHz}$     |             | $C_i$        |      | 40   |      | pF   |
| <b>OUTPUT</b>                                         |                                             |             |              |      |      |      |      |
| Repetitive peak off-state voltage                     | $I_{DRM} = 100\text{ μA}$                   | VO4254D/H/M | $V_{DRM}$    | 400  |      |      | V    |
|                                                       |                                             | VO4256D/H/M | $V_{DRM}$    | 600  |      |      | V    |
| Off-state current                                     | $V_D = V_{DRM}$                             |             | $I_{DRM}$    |      |      | 100  | μA   |
| On-state voltage                                      | $I_T = 300\text{ mA}$                       |             | $V_{TM}$     |      |      | 3    | V    |
| On-current                                            | $PF = 1$ , $V_{T(RMS)} = 1.7\text{ V}$      |             | $I_{TM}$     |      |      | 300  | mA   |
| Critical rate of rise of off-state voltage            | $V_D = 0.67 V_{DRM}$ , $T_J = 25\text{ °C}$ |             | $dV/dt_{cr}$ | 5000 |      |      | V/μs |
| <b>COUPLER</b>                                        |                                             |             |              |      |      |      |      |
| LED trigger current, current required to latch output | $V_D = 3\text{ V}$                          | VO4254D     | $I_{FT}$     |      |      | 1.6  | mA   |
|                                                       |                                             | VO4254H     | $I_{FT}$     |      |      | 2    | mA   |
|                                                       |                                             | VO4254M     | $I_{FT}$     |      |      | 3    | mA   |
|                                                       |                                             | VO4256D     | $I_{FT}$     |      |      | 1.6  | mA   |
|                                                       |                                             | VO4256H     | $I_{FT}$     |      |      | 2    | mA   |
|                                                       |                                             | VO4256M     | $I_{FT}$     |      |      | 3    | mA   |
| Capacitance (input to output)                         | $f = 1\text{ MHz}$ , $V_{IO} = 0\text{ V}$  |             | $C_{IO}$     |      | 0.8  |      | pF   |


### Note

- Minimum and maximum values were tested requirements. Typical values are characteristics of the device and are the result of engineering evaluation. Typical values are for information only and are not part of the testing requirements.

## SAFETY AND INSULATION RATINGS


| PARAMETER                                                                                      | TEST CONDITION | SYMBOL     | MIN. | TYP.      | MAX. | UNIT |
|------------------------------------------------------------------------------------------------|----------------|------------|------|-----------|------|------|
| Climatic classification (according to IEC68 part 1)                                            |                |            |      | 55/100/21 |      |      |
| Pollution degree (DIN VDE 0109)                                                                |                |            |      | 2         |      |      |
| Comparative tracking index per DIN IEC112/VDE 0303 part 1, group IIIa per DIN VDE 6110 175 399 |                |            | 175  |           | 399  |      |
| $V_{IOTM}$                                                                                     |                | $V_{IOTM}$ | 8000 |           |      | V    |
| $V_{IORM}$                                                                                     |                | $V_{IORM}$ | 890  |           |      | V    |
| $P_{SO}$                                                                                       |                | $P_{SO}$   |      |           | 500  | mW   |
| $I_{SI}$                                                                                       |                | $I_{SI}$   |      |           | 250  | mA   |
| $T_{SI}$                                                                                       |                | $T_{SI}$   |      |           | 175  | °C   |
| Creepage distance                                                                              |                |            | 7    |           |      | mm   |
| Clearance distance                                                                             |                |            | 7    |           |      | mm   |

## TYPICAL CHARACTERISTICS ( $T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified)




19660

Fig. 2 - Diode Forward Voltage vs. Forward Current




19682

Fig. 4 - Leakage Current vs. Ambient Temperature



19662

Fig. 3 - Diode Reverse Voltage vs. Temperature



19683

Fig. 5 - On-State Current vs. On-State Voltage




Fig. 6 - Output Off Current (Leakage) vs. Voltage




Fig. 9 - Normalized  $I_H$  vs. Temperature




Fig. 7 - Normalized Trigger Input Current vs. Temperature




Fig. 10 -  $I_{FT}$  vs. LED Pulse Width





Fig. 8 -  $I_{FT}$  vs. Turn-On Time ( $\mu s$ )



**PACKAGE DIMENSIONS** in millimeters



**PACKAGE MARKING** (example)



**Note**

- VDE logo is only marked on option 1 parts. Tape and reel suffix (T) is not part of the package marking.



## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Vishay:](#)

[VO4254D](#) [VO4254D-X006](#) [VO4254D-X007T](#) [VO4254H](#) [VO4254H-X006](#) [VO4254H-X007T](#) [VO4254M](#) [VO4254M-X006](#) [VO4254M-X007T](#) [VO4256D](#) [VO4256D-X006](#) [VO4256D-X007T](#) [VO4256H](#) [VO4256H-X006](#) [VO4256H-X007T](#) [VO4256M](#) [VO4256M-X006](#) [VO4256M-X007T](#) [VO4256D-X001](#)