




REVISIONS

SYM	ECN	DESCRIPTION	DATE	APPROVED
1			09/12/09	

D-SUB TECHNICAL DATA


**SHELL :** Steel 2.5um (100u") min tin over 1.25um (50u") min nickel  
**BODY :** Glass filled thermoplastic.  
 Flame retardant to UL94 V-0 Color Black  
**CONTACTS :** Brass  
 0.1um (4u") min gold over 1.25um (50u") min nickel  
**ELECTRICAL :** Voltage rating : 1000 V RMS at 50 Hz  
 Current rating 7.5A.  
 Insulation resistance >5000 M Ohms  
 Contact resistance 20 mOhms max.  
**MARKING :** Amphenol-...(Series No.)  
 Commercial reference  
 Manufacturing date



RECOMMENDED P.C.B LAYOUT  
(TOLERANCE +/-0.03)

PRODUCT CODE

L 77D D 50 S OL2



# Customer drawing

UNLESS OTHERWISE SPECIFIED		APPROVAL	DATE
TOLERANCES		U.S.	METRIC
.X	+/-		0.50
.XX	+/-		0.30
.XXX	+/-		0.20
FRACTIONS	+/-		5*
ANGLES	+/-		
FOR MATERIALS AND FINISHES		DRAWING FILE :	
SEE NOTES		ANGLE OF PROJECTION	
REMOVE SHARP EDGES			
DIMENSIONS			
U.S.		INCHES	
METRIC		MM	
SIZE DRAWING NO.		REV.	
A4	C L77DD50SOL2		1
SCALE	NONE	SHEET 1	OF 1

Amphenol  
Amphenol East Asia Limited

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Amphenol:](#)

[L77DD50SOL2](#)