### **XUMTANCNM8**

photo-electric sensor - XUM - reflex - Sn 5m - 12..24VDC - M8

Product availability: Stock - Normally stocked in distribution facility



## Main

Commercial Status	Commercialised
Range of product	OsiSense XU
Series name	Application packaging
Electronic sensor type	Photo-electric sensor
Sensor name	XUM
Sensor design	Miniature
Detection system	Reflex
Material	Plastic
Type of output signal	Discrete
Supply circuit type	DC
Wiring technique	3-wire
Discrete output type	NPN
Discrete output function	1 NO or 1 NC programmable
Electrical connection	1 male connector M8, 4 pins
Product specific application	Detection of transparent object
Emission	Infrared reflex
[Sn] nominal sensing distance	3.28 ft (1 m) reflex need reflector XUZC50CR 6.56 ft (2 m) reflex need reflector XUZC50

#### Complementary

Enclosure material	PBT	
Lens material	PC	
Output type	Solid state	
Status LED	LED (orange) for output state     LED (green) for instability	
[Us] rated supply voltage	1224 V DC with reverse polarity protection	
Supply voltage limits	1030 V DC	
Switching capacity in mA	<= 100 mA (overload and short-circuit protection)	
Voltage drop	<= 2 V (closed state)	
Current consumption	<= 10 mA (no-load)	
Delay first up	< 100 ms	
Delay response	< 1 ms	
Setting-up	Sensitivity adjustment	
Depth	0.79 in (20 mm)	
Height	1.3 in (33 mm)	
Length	0.43 in (11 mm)	
Width	0.43 in (11 mm)	
Product weight	0.04 lb(US) (0.02 kg)	

#### Environment

Product certifications	CE CURus
Ambient air temperature for operation	-13131 °F (-2555 °C)
Ambient air temperature for storage	-22158 °F (-3070 °C)
Immunity to ambient light	3000 lux with incandescent light 3000 lux with natural light
Vibration resistance	20 gn, amplitude = +/- 1.5 mm (f = 10500 Hz) conforming to IEC 60068-2-6

Shock resistance	50 gn (duration = 11 ms) conforming to IEC 60068-2-27
IP degree of protection	IP67 conforming to IEC 60529
Ordering and shipping details	
Category	22481 - SENSORS, PHOTOELECTRIC
Discount Schedule	DS2
GTIN	00785901146001
Nbr. of units in pkg.	1
Package weight(Lbs)	0.03
Product availability	Stock - Normally stocked in distribution facility
Returnability	Υ
Country of origin	JP

18 months



Period

# **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Schneider Electric: XUMTANCNM8