

Thyristor Modules


ECO-PAC 2

$$I_{TRMS} = 200 \text{ A}$$

$$I_{TAVM} = 130 \text{ A}$$

$$V_{RRM} = 1200/1600 \text{ V}$$

V_{RSM}	V_{RRM}	
V_{DSM}	V_{DRM}	Typ
V	V	
1300	1200	VCO 132-12io7
1700	1600	VCO 132-16io7



Symbol	Conditions	Maximum Ratings	
I_{TRMS}		200	A
I_{TAVM}	$T_C = 85^\circ\text{C}; T_{VJ} = 130^\circ\text{C}; 180^\circ \text{ sine}$	130	A
I_{TSM}	$T_{VJ} = 45^\circ\text{C}; t = 10 \text{ ms} \quad (50 \text{ Hz})$ $V_R = 0 \quad t = 8.3 \text{ ms} \quad (60 \text{ Hz})$	3600 3850	A A
	$T_{VJ} = 125^\circ\text{C}; t = 10 \text{ ms} \quad (50 \text{ Hz})$ $V_R = 0 \quad t = 8.3 \text{ ms} \quad (60 \text{ Hz})$	3200 3420	A A
I^2t	$T_{VJ} = 45^\circ\text{C}; t = 10 \text{ ms} \quad (50 \text{ Hz})$ $V_R = 0 \quad t = 8.3 \text{ ms} \quad (60 \text{ Hz})$	64 800 62 300	A^2s A^2s
	$T_{VJ} = 125^\circ\text{C}; t = 10 \text{ ms} \quad (50 \text{ Hz})$ $V_R = 0 \quad t = 8.3 \text{ ms} \quad (60 \text{ Hz})$	51 200 49 100	A^2s A^2s
$(di/dt)_{cr}$	$T_{VJ} = 125^\circ\text{C};$ repetitive, $I_T = 250 \text{ A}$ $f = 50 \text{ Hz}; t_p = 200 \mu\text{s};$	150	$\text{A}/\mu\text{s}$
	$V_D = \frac{2}{3} V_{DRM};$ $I_G = 0.5 \text{ A};$ non repetitive, $I_T = I_{TAVM}$ $di_G/dt = 0.5 \text{ A}/\mu\text{s}$	500	$\text{A}/\mu\text{s}$
$(dv/dt)_{cr}$	$T_{VJ} = 125^\circ\text{C}; V_D = \frac{2}{3} V_{DRM};$ $R_{GK} = \infty;$ method 1 (linear voltage rise)	1000	$\text{V}/\mu\text{s}$
P_{GM}	$T_{VJ} = 125^\circ\text{C}; t_p = 30 \text{ ms}$ $I_T = I_{T(AV)M}; t_p = 300 \text{ ms}$	≤ 10 ≤ 5	W W
P_{GAVM}		0.5	W
V_{RGM}		10	V
T_{VJ}		-40...+130	$^\circ\text{C}$
T_{VJM}		150	$^\circ\text{C}$
T_{stg}		-40...+125	$^\circ\text{C}$
V_{ISOL}	50/60 Hz, RMS $I_{ISOL} \leq 1 \text{ mA}$	$t = 1 \text{ min}$ $t = 1 \text{ s}$	3000 3600 V~ V~
M_d	Mounting torque (M4)	1.5 - 2.0 14 - 18	Nm lb.in.
Weight	Typical including screws	24	g

Features

- Isolation voltage 3600 V~
- Planar glass passivated chips
- Low forward voltage drop
- Leads suitable for PC board soldering

Applications

- DC Motor control
- Light and temperature control
- Softstart AC motor controller
- Solid state switches

Advantages

- Easy to mount with two screws
- Space and weight savings
- Improved temperature and power cycling
- High power density
- Small and light weight

Data according to IEC 60747 and refer to a single diode unless otherwise stated.


IXYS reserves the right to change limits, test conditions and dimensions.

20170321a

© 2017 IXYS All rights reserved

1 - 2

Dimensions in mm (1 mm = 0.0394")



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[IXYS:](#)

[VCO132-08io7](#) [VCO132-12io7](#) [VCO132-14io7](#) [VCO132-16io7](#) [VCO132-18io7](#)