

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

**Part Number:** 0022232051  
**Status:** Active  
**Overview:** KK® Interconnect System - Molex  
**Description:** KK 254 Solid Header, Vertical, with Friction Lock, 5 Circuits, Tin (Sn) Plating

**Documents:**  
[3D Model](#)  
[Drawing \(PDF\)](#)  
[Product Specification PS-10-07-001 \(PDF\)](#)  
[Packaging Specification PK-6373-001-000 \(PDF\)](#)  
[RoHS Certificate of Compliance \(PDF\)](#)

|                                |                                 |
|--------------------------------|---------------------------------|
| <b>Agency Certification</b>    |                                 |
| CSA                            | LR19980                         |
| UL                             | E29179                          |
| <b>General</b>                 |                                 |
| Product Family                 | PCB Headers                     |
| Series                         | 6373                            |
| Application                    | Signal, Wire-to-Board           |
| Overview                       | KK® Interconnect System - Molex |
| Product Name                   | KK 254                          |
| UPC                            | 800753590144                    |
| <b>Physical</b>                |                                 |
| Breakaway                      | No                              |
| Circuits (Loaded)              | 5                               |
| Circuits (maximum)             | 5                               |
| Color - Resin                  | Natural (White)                 |
| Durability (mating cycles max) | 25                              |
| First Mate / Last Break        | No                              |
| Flammability                   | 94V-0                           |
| Glow-Wire Capable              | No                              |
| Guide to Mating Part           | No                              |
| Lock to Mating Part            | Yes                             |
| Material - Metal               | Brass                           |
| Material - Plating Mating      | Tin                             |
| Material - Resin               | Nylon                           |
| Net Weight                     | 0.574/g                         |
| Number of Rows                 | 1                               |
| Orientation                    | Vertical                        |
| PC Tail Length                 | 3.56mm                          |
| PCB Locator                    | No                              |
| PCB Retention                  | None                            |
| PCB Thickness - Recommended    | 1.60mm                          |
| Packaging Type                 | Bag                             |
| Pitch - Mating Interface       | 2.54mm                          |
| Pitch - Termination Interface  | 2.54mm                          |
| Polarized to Mating Part       | Yes                             |
| Polarized to PCB               | No                              |
| Shrouded                       | Partial                         |
| Stackable                      | No                              |
| Temperature Range - Operating  | See Product Specification       |
| Termination Interface: Style   | Through Hole                    |
| <b>Electrical</b>              |                                 |
| Current - Maximum per Contact  | 4.0A                            |
| Voltage - Maximum              | 500V                            |
| <b>Solder Process Data</b>     |                                 |



Series image - Reference only

|                                                                          |                   |
|--------------------------------------------------------------------------|-------------------|
| <b>EU ELV</b><br>Not Relevant                                            |                   |
| <b>EU RoHS</b><br>Compliant                                              | <b>China RoHS</b> |
| <b>REACH SVHC</b><br>Not Contained Per -<br>ED/61/2018 (27 June<br>2018) |                   |
| <b>Halogen-Free</b><br><b>Status</b><br>Low-Halogen                      |                   |
| For more information, please visit <a href="#">Contact US</a>            |                   |
| China ROHS                                                               | Green Image       |
| ELV                                                                      | Not Relevant      |
| RoHS Phthalates                                                          | Not Contained     |

**Search Parts in this Series**  
[6373 Series](#)

**Mates With**  
[2695](#) , [6471](#) , [7880](#) , [4455](#) , [7720](#)

|                                                |      |
|------------------------------------------------|------|
| Duration at Max. Process Temperature (seconds) | 005  |
| Lead-freeProcess Capability                    | WAVE |
| Max. Cycles at Max. Process Temperature        | 001  |
| Process Temperature max. C                     | 235  |

**Material Info**

|                    |               |
|--------------------|---------------|
| Engineering Number | A-6373-05A222 |
|--------------------|---------------|

**Reference - Drawing Numbers**

|                         |                                  |
|-------------------------|----------------------------------|
| Packaging Specification | PK-6373-001-000                  |
| Product Specification   | PS-10-07-001                     |
| Sales Drawing           | SD-6373-001-000, SD-6373-001-002 |

This document was generated on 11/29/2018

**PLEASE CHECK [WWW.MOLEX.COM](http://WWW.MOLEX.COM) FOR LATEST PART INFORMATION**

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Molex:](#)

[22-23-2051](#)