

5/8-24UNEF-2A

3/8-32UNEF

2.40 [.095]

3.00 [.118]

16.00 [.630]

7.50 [.296]

31.00 [1.221]

14.10 [.556]

8.65 [.341]

15.80 [.623]

14.10 [.556]

8.65 [.341]

15.80 [.623]

12.7 HEX

2.30 [.091]

9.70 [.382]

8.85 [.349]

RECOMMENDED MOUNTING HOLE DIMENSIONS

				<div>UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS. DIMENSIONS IN [ ] ARE IN INCHES AND FOR CUSTOMER REFERENCE ONLY.</div> <div>UNLESS OTHERWISE SPECIFIED TOLERANCES FOR MILLIMETERS ARE: 0.5 – 8mm ± 0.20mm 8 – 30mm ± 0.40mm 30 – 120mm ± 0.50mm</div> <div>UNLESS OTHERWISE SPECIFIED TOLERANCES FOR INCHES ARE: .020 – .315 = ± 0.007" .315 – 1.180 = ± 0.015" 1.180 – 4.724 = ± 0.020"</div> <div>DO NOT SCALE DRAWING</div>	APPROVALS		DATE		<h1>Amphenol Connex</h1>						
8					DRAWN	GRS	04/08/08								
7					CHECKED			PART DESCRIPTION  N FEMALE BULKHEAD BNC MOUNTING HOLE							
6					ISSUED										
5	HEX NUT	BRASS	NICKEL		1	SHEET	1 OF 1								
4	LOCK WASHER	BRASS	NICKEL		1			PART NO.		172270					
3	CONTACT PIN	PHOS. BRONZE	GOLD		1										
2	INSULATOR	TEFLON	NATURAL		1	CAD FILE		DWG. NO.		172270.DWG	REV.	NC	SIZE	A	SCALE
1	BODY	BRASS	NEXCOTE	1	C:/172/172270.DWG										
DESCRIPTION				MATERIAL	FINISH	QTY									

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Amphenol:](#)

[172270](#)