

STYLE I

STYLE III

- | | |
|---|--|
| 4 | 2.54 μm [.000100] MIN TIN, OVER
2.54 μm [.000100] MIN COPPER. |
| 5 | OBSELETE |
| 6 | D DIMENSION APPLIES TO STYLE II OR STYLE III FERRULES ONLY. |
| 7 | OBSELETE PARTS: OBSELETE CIS STREAMLINING PER D.RENAUD/D.SINISI |

STYLE II

THIS DRAWING IS A CONTROLLED DOCUMENT.						DWG D. BROCKWAY	20MAY04			TE Connectivity	
						CHK C. ROHDE	20MAY04				
DIMENSIONS: mm [INCHES]		TOLERANCES UNLESS OTHERWISE SPECIFIED:		APPROV'D M. WALMSLEY	20MAY04	NAME	FERRULE, INNER, AMPLIMITE HDP-20				
		PRODUCT SPEC		APPLICATION SPEC		SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO		
						A1	00779	 745129	—		
						SEE TABLE			—		
MATERIAL	FINISH		WEIGHT		CUSTOMER DRAWING		SCALE	SHEET	OF	REV	
							4:1	1	1	L2	

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[7-745129-5](#)