

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:	0334710203																																																						
Status:	Active																																																						
Overview:	MX150 Sealed and Unsealed Connector System																																																						
Description:	MX150 Mat-Sealed Female Connector Assembly, Single Row, 2 Circuits, Keying Option C, Dark Gray																																																						
Documents: 3D Model Drawing (PDF) Product Specification PS-33471-000-001 (PDF) Application Specification AS-33472-100-001 (PDF) Application Specification AS-33611-001-001 (PDF) Packaging Specification PK-31300-635-001 (PDF) RoHS Certificate of Compliance (PDF)																																																							
General <table><tr><td>Product Family</td><td>Crimp Housings</td></tr><tr><td>Series</td><td>33471</td></tr><tr><td>Application</td><td>Power, Wire-to-Wire</td></tr><tr><td>Comments</td><td>No Connector Position Assurance (CPA), No Connector Position Assurance (CPA)</td></tr><tr><td>More Detailed Tech Information</td><td>http://uscar.org/guest/teams/10/Electrical-Wiring-Component-Applications -Partnership</td></tr><tr><td>Overview</td><td>MX150 Sealed and Unsealed Connector System</td></tr><tr><td>Product Name</td><td>MX150</td></tr><tr><td>UPC</td><td>883906705237</td></tr></table> Physical <table><tr><td>Circuits (maximum)</td><td>2</td></tr><tr><td>Color - Resin</td><td>Gray (Dark)</td></tr><tr><td>Gender</td><td>Receptacle</td></tr><tr><td>Glow-Wire Capable</td><td>No</td></tr><tr><td>Keying to Mating Part</td><td>Yes</td></tr><tr><td>Lock to Mating Part</td><td>Yes</td></tr><tr><td>Material - Resin</td><td>SPS/Nylon</td></tr><tr><td>Net Weight</td><td>6.305/g</td></tr><tr><td>Number of Rows</td><td>1</td></tr><tr><td>Packaging Type</td><td>Individual Cell</td></tr><tr><td>Panel Mount</td><td>No</td></tr><tr><td>Pitch - Mating Interface</td><td>3.50mm</td></tr><tr><td>Polarized to Mating Part</td><td>Yes</td></tr><tr><td>Stackable</td><td>No</td></tr><tr><td>Temperature Range - Operating</td><td>-40° to +125°C</td></tr></table> Material Info Reference - Drawing Numbers <table><tr><td>Application Specification</td><td>AS-33472-100-001, AS-33611-001-001</td></tr><tr><td>Packaging Specification</td><td>PK-31300-635-001</td></tr><tr><td>Product Specification</td><td>PS-33471-000-001</td></tr><tr><td>Sales Drawing</td><td>150-S-002-1-Z05, SD-33471-0001-001, SD-33471-021</td></tr></table>		Product Family	Crimp Housings	Series	33471	Application	Power, Wire-to-Wire	Comments	No Connector Position Assurance (CPA), No Connector Position Assurance (CPA)	More Detailed Tech Information	http://uscar.org/guest/teams/10/Electrical-Wiring-Component-Applications -Partnership	Overview	MX150 Sealed and Unsealed Connector System	Product Name	MX150	UPC	883906705237	Circuits (maximum)	2	Color - Resin	Gray (Dark)	Gender	Receptacle	Glow-Wire Capable	No	Keying to Mating Part	Yes	Lock to Mating Part	Yes	Material - Resin	SPS/Nylon	Net Weight	6.305/g	Number of Rows	1	Packaging Type	Individual Cell	Panel Mount	No	Pitch - Mating Interface	3.50mm	Polarized to Mating Part	Yes	Stackable	No	Temperature Range - Operating	-40° to +125°C	Application Specification	AS-33472-100-001, AS-33611-001-001	Packaging Specification	PK-31300-635-001	Product Specification	PS-33471-000-001	Sales Drawing	150-S-002-1-Z05, SD-33471-0001-001, SD-33471-021
Product Family	Crimp Housings																																																						
Series	33471																																																						
Application	Power, Wire-to-Wire																																																						
Comments	No Connector Position Assurance (CPA), No Connector Position Assurance (CPA)																																																						
More Detailed Tech Information	http://uscar.org/guest/teams/10/Electrical-Wiring-Component-Applications -Partnership																																																						
Overview	MX150 Sealed and Unsealed Connector System																																																						
Product Name	MX150																																																						
UPC	883906705237																																																						
Circuits (maximum)	2																																																						
Color - Resin	Gray (Dark)																																																						
Gender	Receptacle																																																						
Glow-Wire Capable	No																																																						
Keying to Mating Part	Yes																																																						
Lock to Mating Part	Yes																																																						
Material - Resin	SPS/Nylon																																																						
Net Weight	6.305/g																																																						
Number of Rows	1																																																						
Packaging Type	Individual Cell																																																						
Panel Mount	No																																																						
Pitch - Mating Interface	3.50mm																																																						
Polarized to Mating Part	Yes																																																						
Stackable	No																																																						
Temperature Range - Operating	-40° to +125°C																																																						
Application Specification	AS-33472-100-001, AS-33611-001-001																																																						
Packaging Specification	PK-31300-635-001																																																						
Product Specification	PS-33471-000-001																																																						
Sales Drawing	150-S-002-1-Z05, SD-33471-0001-001, SD-33471-021																																																						



EU ELV Compliant	
EU RoHS Compliant REACH SVHC Not Contained Per -ED/88/2018 (15 January 2019) Halogen-Free Status Not Relevant	China RoHS
For more information, please visit Contact US	
China ROHS ELV RoHS Phthalates	Not Relevant Compliant Not Contained

Search Parts in this Series
33471 Series

Mates With
MX150 Sealed Single Row Male Connector
33481

Use With
MX150 Female Terminal [33012](#) , [33001](#)

MX150 Sealed Receptacle Cavity
Plug [343454001](#)
MX150 Backshell
[349490210](#) , [349490220](#)

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Molex:](#)

[33471-0203](#)