

MM24-5RD

Features

- High Gain 5.5dBi Antenna
- Strong Non-Skid Magnetic Base
- Versatile Mounting: Desktop, Wall, Ceiling, File Cabinet
- 5' Low Loss Cable
- Removable Antenna, Weatherproof Base
- MC Card, MMCX, RMMCX, RPSMA, RPTNC, U.FL

Specifications

<i>Operating Frequency</i>	2400 to 2485 MHz
<i>Antenna Gain</i>	5.5 dBi
<i>System Gain (After Cable/Connector Loss)</i>	4.5 dBi
<i>VSWR</i>	1.5:1
<i>Impedance</i>	50 Ohm
<i>Max Input Power</i>	10W
<i>Cable Length</i>	5 feet (1.5 M)
<i>Connector Options</i>	MMCX, RMMCX, MC Card, RPSMA, RPTNC, U.FL
<i>Operating Temperature</i>	0 to 60 Deg C
<i>Antenna Size</i>	7.75 x 0.5D inches (197 x 12.7D mm)
<i>Mount Size</i>	2 x 1.6 inches (51 x 41 mm)
<i>Weight</i>	7.2 oz (204 g)



System Ordering:

MM24-5RD-□□□□ 2.4GHz 5dbi Micro Mag Antenna/Mount

Connector Options:

- MC = MC Card
- MMCX = MMCX
- RMMCX = Reverse Polarity MMCX
- RPSMA = Reverse Polarity SMA
- RPTNC = Reverse Polarity TNC
- UFL = U.FL / MHF

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Laird Connectivity:](#)

[MM24-5RD-MMCX](#)