



Product: <u>83049</u> ☑

Lead Wire, #22 Str SPC, TFE Ins, AWM 1371 105C TYPE ET

Product Description

High Temp Plastic Lead Wire, 22AWG (7x30) Silver Plated Copper, TFE Insulation, AWM 1371 105C TYPE ET MIL-W-16878/6 250V 200C

Technical Specifications

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Material	No. of Conductors
22	7x30	SC - Silvered Copper	1
Condu	uctor Count:		1

Insulation

Material	Nominal Diameter	Nominal Wall Thickness
PTFE - Polytetrafluoroethylene	0.042 in	0.006 in

Electrical Characteristics

Current

Max. Recommended Current [A]

Voltage

Non-UL Voltage Rating 250 V

Temperature Range

Non-UL Temp Rating:	200°C
UL Temp Rating:	105°C

Mechanical Characteristics

Bulk Cable Weight: 3 lbs/1000ft

Standards

UL AWM Style:	1371
Military Specification:	NEMA HP3, MIL-W-16878/6

Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes

EU RoHS Compliance Date (yyyy-mm-dd):	2005-04-01
MII Order #39 (China RoHS):	Yes

Flammability, LS0H, Toxicity Testing

UL Flammability:	VW-1
UL voltage rating:	600 V RMS

Plenum/Non-Plenum

|--|

Part Number

Variants

Item #	Color	Putup Type	Length	UPC
83049 010100	Black	Reel	100 ft	
83049 0101000	Black	Reel	1,000 ft	612825354925
83049 006100	Blue, Light	Reel	100 ft	
83049 0061000	Blue, Light	Reel	1,000 ft	
83049 0011000	Brown			
83049 001100	Brown	Reel	100 ft	
83049 008100	Gray			
83049 0081000	Gray	Reel	1,000 ft	612825399698
83049 005100	Green, Dark			
83049 003100	Orange	Reel	100 ft	
83049 0031000	Orange	Reel	1,000 ft	
83049 002100	Red	Reel	100 ft	
83049 0021000	Red	Reel	1,000 ft	612825353836
83049 007100	Violet	Reel	100 ft	
83049 009100	White	Reel	100 ft	
83049 0091000	White	Reel	1,000 ft	612825399704
83049 004100	Yellow	Reel	100 ft	
83049 0041000	Yellow	Reel	1,000 ft	

Footnote:	E - MAY CONTAIN MORE THAN 1 PIECE. MINIMUM LENGTH OF ANY ONE PIECE IS 25'.
Footnote:	S - STRIPING ADDERS FOR TYPES E AND EE: 1, 2, 3 STRIPES. MINIMUM ORDER 10,000' PER STRIPE COMBINATION. (SEE STRIPING ADDER TABLE)

History

Update and Revision:	Revision Number: 0.269 Revision Date: 04-28-2020	

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Belden Wire & Cable:

<u>83049 010100</u> <u>83049 0101000</u> <u>83049 006100</u> <u>83049 001100</u> <u>83049 005100</u> <u>83048 0031000</u> <u>83049 003100</u> <u>83049 002100</u> <u>83049 0021000</u> <u>83049 007100</u> <u>83049 009100</u> <u>83049 0091000</u> <u>83049 004100</u> <u>83049 008100</u> <u>83049 008100</u> <u>83049 0011000</u>