

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: [0465561745](#)
Status: **Active**
Overview: [SEARAY* Slim](#)
Description: Searay Slim Plug, 40 Circuits, 7.00mm Unmated Height, 4 Rows, with Pegs, Solder Charge Lead-Free

Documents:

| | |
|--|--|
| 3D Model | Application Specification AS-45970-990-001 (PDF) |
| Drawing (PDF) | Packaging Specification PK-45970-002-001 (PDF) |
| Product Specification PS-45970-001-001 (PDF) | Test Summary TS-45970-002-001 (PDF) |
| Application Specification AS-45970-001 (PDF) | RoHS Certificate of Compliance (PDF) |
| Application Specification AS-45970-002-001 (PDF) | |

Agency Certification


| | |
|-----|---------|
| CSA | LR19980 |
| UL | E29179 |

General

| | |
|----------------------|------------------------------|
| Product Family | PCB Headers |
| Series | 46556 |
| 3D Viewer | Yes |
| Application | Board-to-Board, Signal |
| CURRENT-MAX-NUMERIC | 2.7 |
| Electrical Model | Yes |
| Overview | SEARAY* Slim |
| PITCH-MATING-NUMERIC | 1.27 |
| Product Name | SEARAY |
| UPC | 883906481704 |

Physical

| | |
|--------------------------------|--------------------------------|
| Breakaway | No |
| Circuits (Loaded) | 40 |
| Circuits (maximum) | 40 |
| Color - Resin | Black |
| Durability (mating cycles max) | 100 |
| First Mate / Last Break | No |
| Flammability | 94V-0 |
| Glow-Wire Capable | No |
| Guide to Mating Part | Yes |
| Keying to Mating Part | Yes |
| Lock to Mating Part | None |
| Material - Metal | Copper Alloy |
| Material - Plating Mating | Gold |
| Material - Plating Termination | Tin |
| Material - Resin | High Temperature Thermoplastic |
| Net Weight | 1.242/g |
| Number of Rows | 4 |
| Orientation | Vertical |
| PCB Locator | Yes |
| PCB Retention | Yes |
| PCB Thickness - Recommended | 1.60mm |
| Packaging Type | Embossed Tape on Reel |
| Pitch - Mating Interface | 1.27mm |
| Pitch - Termination Interface | 1.27mm |
| Plating min - Mating | 0.762µm |
| Polarized to Mating Part | Yes |
| Polarized to PCB | Yes |



Series image - Reference only

EU ELV

Not Relevant

EU RoHS

Compliant

REACH SVHC

Not Contained Per - ED/71/2019 (16 July 2019)

Halogen-Free

Status

Low-Halogen

For more information, please visit [Contact US](#)

China ROHS

ELV

RoHS Phthalates

China RoHS

Green Image

Not Relevant

Not Contained

Search Parts in this Series

[46556](#) Series

Mates With

[46557](#) SEARAY Slim Receptacles

| | |
|--------------------------------|--------------------|
| Robotic Placement | Pick and Place Cap |
| Shrouded | No |
| Stackable | No |
| Surface Mount Compatible (SMC) | Yes |
| Temperature Range - Operating | -55° to +125°C |
| Termination Interface: Style | Surface Mount |
| Unmated Height | 7.00mm |

Electrical

| | |
|-------------------------------|---------|
| Current - Maximum per Contact | 2.7A |
| Voltage - Maximum | 240V AC |

Solder Process Data

| | |
|--|--------|
| Duration at Max. Process Temperature (seconds) | 020 |
| Lead-free Process Capability | REFLOW |
| Max. Cycles at Max. Process Temperature | 003 |
| Process Temperature max. C | 260 |

Material Info**Reference - Drawing Numbers**

| | |
|---------------------------|--|
| Application Specification | AS-45970-001, AS-45970-002-001, AS-45970-990-001 |
| Electrical Model Document | EE-45970-010 |
| Packaging Specification | PK-45970-002-001 |
| Product Specification | PS-45970-001-001 |
| S-Parameter Model | SP-45970-010 |
| Sales Drawing | SD-46556-001-001 |
| Symbol/Footprint Data | SYM-46556-1745 |
| Test Summary | TS-45970-002-001 |

This document was generated on 10/02/2019

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Molex:](#)

[46556-1745](#)