

# BCP56 Series, SBCP56 Series

## NPN Silicon Epitaxial Transistor

These NPN Silicon Epitaxial transistors are designed for use in audio amplifier applications. The device is housed in the SOT-223 package, which is designed for medium power surface mount applications.

### Features

- High Current: 1.0 A
- The SOT-223 package can be soldered using wave or reflow. The formed leads absorb thermal stress during soldering, eliminating the possibility of damage to the die
- Available in 12 mm Tape and Reel  
Use BCP56T1 to Order the 7 inch/1000 Unit Reel  
Use BCP56T3 to Order the 13 inch/4000 Unit Reel
- PNP Complement is BCP53T1
- AEC-Q101 Qualified and PPAP Capable
- S Prefix for Automotive and Other Applications Requiring Unique Site and Control Change Requirements
- These Devices are Pb-Free, Halogen Free/BFR Free and are RoHS Compliant

### MAXIMUM RATINGS ( $T_C = 25^\circ\text{C}$ unless otherwise noted)

| Rating  | Symbol         | Value      | Unit                      |
|---|----------------|------------|---------------------------|
| Collector-Emitter Voltage   | $V_{CEO}$      | 80         | Vdc                       |
| Collector-Base Voltage  | $V_{CBO}$      | 100        | Vdc                       |
| Emitter-Base Voltage  | $V_{EBO}$      | 5          | Vdc                       |
| Collector Current   | $I_C$          | 1          | Adc                       |
| Total Power Dissipation<br>@ $T_A = 25^\circ\text{C}$ (Note 1)<br>Derate above $25^\circ\text{C}$ | $P_D$          | 1.5<br>12  | W<br>mW/ $^\circ\text{C}$ |
| Operating and Storage<br>Temperature Range  | $T_J, T_{stg}$ | -65 to 150 | $^\circ\text{C}$          |

### THERMAL CHARACTERISTICS

| Characteristic   | Symbol          | Max       | Unit                      |
|--|-----------------|-----------|---------------------------|
| Thermal Resistance,<br>Junction-to-Ambient<br>(surface mounted)      | $R_{\theta JA}$ | 83.3      | $^\circ\text{C}/\text{W}$ |
| Maximum Temperature for<br>Soldering Purposes<br>Time in Solder Bath | $T_L$           | 260<br>10 | $^\circ\text{C}$<br>Sec   |

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.



1. Device mounted on a FR-4 glass epoxy printed circuit board 1.575 in x 1.575 in x 0.0625 in; mounting pad for the collector lead = 0.93 sq in.



**ON Semiconductor®**


<http://onsemi.com>

## MEDIUM POWER NPN SILICON HIGH CURRENT TRANSISTOR SURFACE MOUNT



**SOT-223  
CASE 318E  
STYLE 1**

### MARKING DIAGRAM



xx = Specific Device Code  
A = Assembly Location  
Y = Year  
W = Work Week  
■ = Pb-Free Package  
(Note: Microdot may be in either location)

### ORDERING INFORMATION

See detailed ordering and shipping information in the package dimensions section on page 2 of this data sheet.

## BCP56 Series, SBCP56 Series

### ELECTRICAL CHARACTERISTICS (T<sub>A</sub> = 25°C unless otherwise noted)

| Characteristics  | Symbol               | Min | Typ | Max | Unit |
|--|----------------------|-----|-----|-----|------|
| <b>OFF CHARACTERISTICS</b>   |                      |     |     |     |      |
| Collector–Base Breakdown Voltage<br>(I <sub>C</sub> = 100 µAdc, I <sub>E</sub> = 0)    | V <sub>(BR)CBO</sub> | 100 | –   | –   | Vdc  |
| Collector–Emitter Breakdown Voltage<br>(I <sub>C</sub> = 1.0 mAdc, I <sub>B</sub> = 0) | V <sub>(BR)CEO</sub> | 80  | –   | –   | Vdc  |
| Emitter–Base Breakdown Voltage<br>(I <sub>E</sub> = 10 µAdc, I <sub>C</sub> = 0)       | V <sub>(BR)EBO</sub> | 5.0 | –   | –   | Vdc  |
| Collector–Base Cutoff Current<br>(V <sub>CB</sub> = 30 Vdc, I <sub>E</sub> = 0)        | I <sub>CBO</sub>     | –   | –   | 100 | nAdc |
| Emitter–Base Cutoff Current<br>(V <sub>EB</sub> = 5.0 Vdc, I <sub>C</sub> = 0)         | I <sub>EBO</sub>     | –   | –   | 10  | µAdc |

### ON CHARACTERISTICS (Note 2)

|   |                      |                             |                       |                             |     |
|---|----------------------|-----------------------------|-----------------------|-----------------------------|-----|
| DC Current Gain<br>(I <sub>C</sub> = 5.0 mA, V <sub>CE</sub> = 2.0 V) All Part Types<br>(I <sub>C</sub> = 150 mA, V <sub>CE</sub> = 2.0 V) BCP56T1, SBCP56T1, SBCP56T3<br>BCP56–10T1, SBCP56–10T1<br>BCP56–16T1, SBCP56–16T1, SBCP56–16T3<br>(I <sub>C</sub> = 500 mA, V <sub>CE</sub> = 2.0 V) All Types | h <sub>FE</sub>      | 25<br>40<br>63<br>100<br>25 | –<br>–<br>–<br>–<br>– | –<br>250<br>160<br>250<br>– | –   |
| Collector–Emitter Saturation Voltage<br>(I <sub>C</sub> = 500 mAdc, I <sub>B</sub> = 50 mAdc)   | V <sub>CE(sat)</sub> | –                           | –                     | 0.5                         | Vdc |
| Base–Emitter On Voltage<br>(I <sub>C</sub> = 500 mAdc, V <sub>CE</sub> = 2.0 Vdc)   | V <sub>BE(on)</sub>  | –                           | –                     | 1.0                         | Vdc |

### DYNAMIC CHARACTERISTICS

|   |                |   |     |   |     |
|---|----------------|---|-----|---|-----|
| Current–Gain – Bandwidth Product<br>(I <sub>C</sub> = 10 mAdc, V <sub>CE</sub> = 5.0 Vdc, f = 35 MHz) | f <sub>T</sub> | – | 130 | – | MHz |
|---|----------------|---|-----|---|-----|

2. Pulse Test: Pulse Width ≤ 300 µs, Duty Cycle ≤ 2.0%

### ORDERING INFORMATION

| Device       | Marking | Package              | Shipping <sup>†</sup> |
|--------------|---------|----------------------|-----------------------|
| BCP56T1G     | BH      | SOT–223<br>(Pb–Free) | 1000 / Tape & Reel    |
| SBCP56T1G    |         |                      |                       |
| BCP56T3G     | BH      | SOT–223<br>(Pb–Free) | 4000 / Tape & Reel    |
| SBCP56T3G    |         |                      |                       |
| BCP56–10T1G  | BH–10   | SOT–223<br>(Pb–Free) | 1000 / Tape & Reel    |
| SBCP56–10T1G |         |                      |                       |
| BCP56–16T1G  | BH–16   | SOT–223<br>(Pb–Free) | 1000 / Tape & Reel    |
| SBCP56–16T1G |         |                      |                       |
| BCP56–16T3G  | BH–16   | SOT–223<br>(Pb–Free) | 4000 / Tape & Reel    |
| SBCP56–16T3G |         |                      |                       |

<sup>†</sup>For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

# BCP56 Series, SBCP56 Series

## TYPICAL ELECTRICAL CHARACTERISTICS




Figure 1. DC Current Gain




Figure 2. Current-Gain - Bandwidth Product




Figure 3. Capacitance




Figure 4. Collector Emitter Saturation Voltage vs. Collector Current






Figure 5. Base Emitter Saturation Voltage vs. Collector Current

# BCP56 Series, SBCP56 Series


## TYPICAL ELECTRICAL CHARACTERISTICS




**Figure 6. Base Emitter Voltage vs. Collector Current**



**Figure 7. Collector Saturation Region**



**Figure 8. Safe Operating Area**





**Figure 9. Power Derating Curve**

# BCP56 Series, SBCP56 Series

## PACKAGE DIMENSIONS

SOT-223 (TO-261)  
CASE 318E-04  
ISSUE N



### NOTES:


1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
2. CONTROLLING DIMENSION: INCH.

| DIM | MILLIMETERS |      |      | INCHES |       |       |
|-----|-------------|------|------|--------|-------|-------|
|     | MIN         | NOM  | MAX  | MIN    | NOM   | MAX   |
| A   | 1.50        | 1.63 | 1.75 | 0.060  | 0.064 | 0.068 |
| A1  | 0.02        | 0.06 | 0.10 | 0.001  | 0.002 | 0.004 |
| b   | 0.60        | 0.75 | 0.89 | 0.024  | 0.030 | 0.035 |
| b1  | 2.90        | 3.06 | 3.20 | 0.115  | 0.121 | 0.126 |
| c   | 0.24        | 0.29 | 0.35 | 0.009  | 0.012 | 0.014 |
| D   | 6.30        | 6.50 | 6.70 | 0.249  | 0.256 | 0.263 |
| E   | 3.30        | 3.50 | 3.70 | 0.130  | 0.138 | 0.145 |
| e   | 2.20        | 2.30 | 2.40 | 0.087  | 0.091 | 0.094 |
| e1  | 0.85        | 0.94 | 1.05 | 0.033  | 0.037 | 0.041 |
| L   | 0.20        | ---  | ---  | 0.008  | ---   | ---   |
| L1  | 1.50        | 1.75 | 2.00 | 0.060  | 0.069 | 0.078 |
| H_E | 6.70        | 7.00 | 7.30 | 0.264  | 0.276 | 0.287 |
| θ   | 0°          | ---  | 10°  | 0°     | ---   | 10°   |


### STYLE 1:

1. BASE
2. COLLECTOR
3. EMITTER
4. COLLECTOR

## SOLDERING FOOTPRINT\*



\*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

ON Semiconductor and  are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## PUBLICATION ORDERING INFORMATION

### LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor  
P.O. Box 5163, Denver, Colorado 80217 USA  
Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada  
Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada  
Email: [orderlit@onsemi.com](mailto:orderlit@onsemi.com)

N. American Technical Support: 800-282-9855 Toll Free  
USA/Canada

Europe, Middle East and Africa Technical Support:  
Phone: 421 33 790 2910

Japan Customer Focus Center  
Phone: 81-3-5817-1050

ON Semiconductor Website: [www.onsemi.com](http://www.onsemi.com)

Order Literature: <http://www.onsemi.com/orderlit>

For additional information, please contact your local  
Sales Representative

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[ON Semiconductor:](#)

[BCP56-10T1](#) [BCP56-16T1](#) [BCP56-16T3](#) [BCP56T1](#) [BCP56T3](#)