


N-Channel 200 V (D-S) MOSFET


PRODUCT SUMMARY			
V _{DS} (V)	R _{DS(on)} (Ω)	I _D (A)	Q _g (Typ.)
200	0.053 at V _{GS} = 15 V	36	57
	0.054 at V _{GS} = 10 V	36	

FEATURES

- TrenchFET® Power MOSFETs
- 175 °C Junction Temperature
- 100 % R_g and UIS Tested
- Compliant to RoHS Directive 2002/95/EC


TO-263


Top View


Ordering Information: SUM36N20-54P-E3 (Lead (Pb)-free)

N-Channel MOSFET

ABSOLUTE MAXIMUM RATINGS T_C = 25 °C, unless otherwise noted

Parameter	Symbol	Limit	Unit
Drain-Source Voltage	V _{DS}	200	V
Gate-Source Voltage	V _{GS}	± 25	
Continuous Drain Current (T _J = 175 °C)	I _D	36	A
		22.6	
Pulsed Drain Current	I _{DM}	80	
Single Pulse Avalanche Current	I _{AS}	20	
Single Pulse Avalanche Energy ^a	E _{AS}	20	mJ
Maximum Power Dissipation ^a	P _D	166 ^b	W
		3.12	
Operating Junction and Storage Temperature Range	T _J , T _{stg}	- 55 to 175	°C

THERMAL RESISTANCE RATINGS

Parameter	Symbol	Limit	Unit
Junction-to-Ambient (PCB Mount) ^c	R _{thJA}	40	°C/W
Junction-to-Case (Drain)	R _{thJC}	0.75	

Notes:

a. Duty cycle ≤ 1 %.

b. See SOA curve for voltage derating.

c. When mounted on 1" square PCB (FR-4 material).







SPECIFICATIONS $T_J = 25^\circ\text{C}$, unless otherwise noted

Parameter	Symbol	Test Conditions	Min.	Typ.	Max.	Unit
Static						
Drain-Source Breakdown Voltage	V_{DS}	$V_{GS} = 0 \text{ V}, I_D = 250 \mu\text{A}$	200			V
Gate Threshold Voltage	$V_{GS(\text{th})}$	$V_{DS} = V_{GS}, I_D = 250 \mu\text{A}$	2.5		4.5	
Gate-Body Leakage	I_{GSS}	$V_{DS} = 0 \text{ V}, V_{GS} = \pm 20 \text{ V}$			± 100	nA
		$V_{DS} = 0 \text{ V}, V_{GS} = \pm 25 \text{ V}$			± 300	
Zero Gate Voltage Drain Current	I_{DSS}	$V_{DS} = 200 \text{ V}, V_{GS} = 0 \text{ V}$		1		μA
		$V_{DS} = 200 \text{ V}, V_{GS} = 0 \text{ V}, T_J = 100^\circ\text{C}$		25		
		$V_{DS} = 200 \text{ V}, V_{GS} = 0 \text{ V}, T_J = 150^\circ\text{C}$		250		
On-State Drain Current ^a	$I_{D(\text{on})}$	$V_{DS} \geq 10 \text{ V}, V_{GS} = 10 \text{ V}$	40			A
Drain-Source On-State Resistance ^a	$R_{DS(\text{on})}$	$V_{GS} = 10 \text{ V}, I_D = 20 \text{ A}$		0.044	0.054	Ω
		$V_{GS} = 15 \text{ V}, I_D = 20 \text{ A}$		0.0435	0.053	
		$V_{GS} = 10 \text{ V}, I_D = 20 \text{ A}, T_J = 100^\circ\text{C}$			0.098	
		$V_{GS} = 10 \text{ V}, I_D = 20 \text{ A}, T_J = 150^\circ\text{C}$			0.130	
Forward Transconductance ^a	g_{fs}	$V_{DS} = 15 \text{ V}, I_D = 20 \text{ A}$	25			S
Dynamic^b						
Input Capacitance	C_{iss}	$V_{GS} = 0 \text{ V}, V_{DS} = 25 \text{ V}, f = 1 \text{ MHz}$		3100		pF
Output Capacitance	C_{oss}			300		
Reverse Transfer Capacitance	C_{rss}			135		
Total Gate Charge ^c	Q_g	$V_{DS} = 100 \text{ V}, V_{GS} = 15 \text{ V}, I_D = 50 \text{ A}$		85	127	nC
Gate-Source Charge ^c	Q_{gs}	$V_{DS} = 100 \text{ V}, V_{GS} = 10 \text{ V}, I_D = 50 \text{ A}$		57	85	
Gate-Drain Charge ^c	Q_{gd}			14		
Gate Resistance	R_g		$f = 1 \text{ MHz}$	20		
Turn-On Delay Time ^c	$t_{d(\text{on})}$	$V_{DD} = 100 \text{ V}, R_L = 2 \Omega$ $I_D \geq 50 \text{ A}, V_{GEN} = 10 \text{ V}, R_g = 1 \Omega$		1.2	2	Ω
Rise Time ^c	t_r			16	25	ns
Turn-Off Delay Time ^c	$t_{d(\text{off})}$			170	260	
Fall Time ^c	t_f			27	42	
Source-Drain Diode Ratings and Characteristics $T_C = 25^\circ\text{C}^b$						
Continuous Current	I_S	$I_F = 20 \text{ A}, V_{GS} = 0 \text{ V}$ $I_F = 40 \text{ A}, dI/dt = 100 \text{ A}/\mu\text{s}$			36	A
Pulsed Current	I_{SM}				80	
Forward Voltage ^a	V_{SD}			0.86	1.5	V
Reverse Recovery Time	t_{rr}			116	175	ns
Peak Reverse Recovery Current	$I_{RM(\text{REC})}$			9	14	A
Reverse Recovery Charge	Q_{rr}			0.53	0.8	μC
Reverse Recovery Fall Time	t_a			84		nS
Reverse Recovery Rise Time	t_b			32		

Notes:

a. Pulse test; pulse width $\leq 300 \mu\text{s}$, duty cycle $\leq 2\%$.
b. Guaranteed by design, not subject to production testing.
c. Independent of operating temperature.

Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.







TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted





SUM36N20-54P

Vishay Siliconix



TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted



THERMAL RATINGS

Maximum Drain Current vs. Case Temperature

Safe Operating Area

Normalized Thermal Transient Impedance, Junction-to-Case

Vishay Siliconix maintains worldwide manufacturing capability. Products may be manufactured at one of several qualified locations. Reliability data for Silicon Technology and Package Reliability represent a composite of all qualified locations. For related documents such as package/tape drawings, part marking, and reliability data, see www.vishay.com/ppg?74295.

Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.