



RECOMMENDED MOUNTING HOLE PATTERN FOR .063 THICK P.C. BOARD

- 1 POST TO WITHSTAND 13 NEWTONS (3LBS.) MIN. AXIAL FORCE IN BOTH DIRECTIONS SHOWN WITHOUT DISLODGING.
- 2 TOLERANCES APPLY TO SOLDER SIDE OF BOARD.
- 3 MEASURED AT SURFACE -A-.
- 4 PLASTIC FLASH PERMITTED IN THIS AREA.
- 5 PARTS COMPLY WITH AMP SOLDERABILITY SPEC. NO. 109-11-2.
- 6 ONE HOLE MAY BE UNDERSIZED (.051/.046 DIA.) FOR ASSEMBLY RETENTION DURING WAVE SOLDERING.
- 7 MATERIAL: HEADER-THERMOPLASTIC POLYESTER GLASS-FILLED 94V-0(NATURAL) POST-COPPER ALLOY (TIN PLATED)
- 8 COORDINATE DIMENSION APPLIES FROM CENTER OF ACTUAL FEATURE.
- 9 PLASTIC BURRS CAUSED BY CUT-OFF TOOLING ARE PERMITTED WITHIN THE MAXIMUM TOLERANCE ENVELOPE.
- 10 POST TO BE MEASURED WHEN STRIP IS HELD FLAT.
- 11 POST MUST WITHSTAND TWO 90° BENDS AGAINST EXTRUSION WITHOUT BREAKING.
- 12 DIMENSION SHOULD BE .140 MIN WHEN MATING WITH A MTA 156 CONNECTOR ASSEMBLY OR A SL-156 CONNECTOR ASSEMBLY.
- 13 PIN BURR OF .005 MAX. VERTICAL AND .003 MAX. HORIZONTAL PERMITTED AT POST TIPS ON BOTH ENDS.

	IN	MM	NUMBER OF POSITIONS	PART NUMBER
OBSOLETE	3.744	95.10	24	-2-640384-4
	3.588	91.14	23	-2-640384-3
	3.432	87.17	22	-2-640384-2
	3.276	83.21	21	-2-640384-1
	3.120	79.25	20	2-640384-0
	2.964	75.29	19	1-640384-9
	2.808	71.32	18	1-640384-8
	2.652	67.36	17	1-640384-7
	2.496	63.40	16	1-640384-6
	2.340	59.44	15	1-640384-5
	2.184	55.47	14	1-640384-4
	2.028	51.51	13	1-640384-3
	1.872	47.55	12	1-640384-2
	1.716	43.59	11	1-640384-1
	1.560	39.62	10	1-640384-0
	1.404	35.66	9	640384-9
	1.248	31.70	8	640384-8
	1.092	27.74	7	640384-7
	.936	23.77	6	640384-6
	.780	19.81	5	640384-5
	.624	15.85	4	640384-4
	.468	11.89	3	640384-3
	.312	7.92	2	640384-2
	IN	MM		

IN	MM	IN	MM
.051	1.30	-	-
.046	1.17	-	-
.045	1.14	1.000	25.40
.030	0.76	.700	17.78
.018	0.46	.450	11.43
.015	0.38	.250	6.35
.012	0.30	.156	3.96
.010	0.25	.140	3.56
.008	0.20	.125	3.18
.005	0.13	.078	1.98
.003	0.08	.063	1.60
.001	0.03	.060	1.52
IN	MM	IN	MM

CONVERSION TABLE

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: INCHES	TOLERANCES UNLESS OTHERWISE SPECIFIED:	DIN B LEWIS 14OCT92	14OCT92	TE Connectivity
0 PLC ± -	1 PLC ± -	2 PLC ± -	3 PLC ± .005	4 PLC ANGLES ± -
APPROVED: R SWING 14JAN93	APPROVED: R SPEER 14JAN93	NAME	MTA-156 HEADER ASSEMBLY, PLAIN, STRAIGHT, .045 ROUND POST, TIN PLATED	RESTRICTED TO
MATERIAL	FINISH	WEIGHT	SIZE: A1 00779	SCALE: 5:1
			DRAWING NO: 640384	SHEET 1 OF 1
			CUSTOMER DRAWING	REV AB

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[640384-5](#)