

MSTBA 2,5/6-G-5,08 PIN 9,5 - 1825254

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)

PCB headers, nominal current: 12 A, number of positions: 6, pitch: 5.08 mm, color: green, contact surface: Tin, mounting: Wave soldering



The figure shows a 10-position version of the product

Your advantages

- Maximum flexibility when it comes to device design one header for connectors with different connection technologies
- Well-known mounting principle allows worldwide use
- ☑ Plug-in direction parallel to the PCB
- Closed contour for optimum stability of the plug-in connection



Key Commercial Data

Packing unit	50 pc		
GTIN	4 046356 804691		
GTIN	4046356804691		

Technical data

Dimensions

Length [1]	12 mm
Width	32.48 mm
Pitch	5.08 mm
Dimension a	25.4 mm
Width [w]	32.48 mm
Height [h]	18.1 mm
Height	8.6 mm
Length of the solder pin	9.5 mm
Pin dimensions	1 x 1 mm
Length	12 mm

General



MSTBA 2,5/6-G-5,08 PIN 9,5 - 1825254

Technical data

General

Range of articles	MSTBA 2,5/G		
Rated voltage (III/3)	250 V		
Connection in acc. with standard	EN-VDE		
Nominal current I _N	12 A		
Color	green		
Number of positions	6		

Standards and Regulations

Connection in acc. with standard	EN-VDE

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e		
	No hazardous substances above threshold values		

Approvals

Α	n	n	rc	v	a	ļs

Approvals

EAC

Ex Approvals

Approval details

EAC **EHI** B.01742

Phoenix Contact 2018 © - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany Tel. +49 5235 300

Fax +49 5235 300

http://www.phoenixcontact.com

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Phoenix Contact: 1825254