


Mini-Size Gender Changer

157-0300, 157-0304, 157-0308

KOBICONN

Mini-Size Gender Changer



DIMENSIONS: mm

MOUSER STOCK NO.	Number of Contacts	Dimensions: mm (in.)			
		A	B	C	D
157-0300	9	30.8 (1.21)	25.0 (.984)	16.92 (.666)	16.92 (.666)
157-0304	15	39.2 (1.54)	33.3 (1.31)	25.25 (.994)	25.25 (.994)
157-0308	25	53.05 (2.09)	47.04 (1.85)	38.96 (1.53)	38.96 (1.53)

SPECIFICATIONS

Type:	Male/Male
Insulator:	PBT glass fiber reinforced
Contact:	Brass
Contact Plating:	Gold over nickel
Shell:	Tin plated
Screw:	UNC #4-10 hexscrew
Current Rating:	3A
Dielectric Strength:	1000VAC for 1 minute
Insulator Resistance:	1000MΩ min. @500VDC
Temperature:	-55°C ~ +105°C

Date Last Revised: 08-25-11

Available from Mouser Electronics
1-800-346-6873 / www.mouser.com

KC-300688

Specifications are subject to change without notice. No liability or warranty implied by this information. Environmental compliance based on producer documentation.

157-0300, 157-0304, 157-0308

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Kobiconn:

[157-0308](#) [157-0300](#) [157-0304](#)