



File: E209153



ISO9001:2008 Certified

**Mechanical Specifications (mm)**

D:	15.0	± Max
T:	5.0	± Max
Lead Diameter	0.8	± Nom
S:	7.8	± Nom
L:	38.0	± min
Coating Lead Run Down (straight Leads)		±
B:	4.00	± 1
C:	43.50	± max



**Electrical Specifications**

Resistance:	40.0 Ω	± 20 %
Max Steady State Current upto 65°C:	4.00	A
Max Rec. Energy Rating:	35	J
Actual Failure Instantaneous Energy:	70	J
Resistance @ 100% Max Current:	0.30	Ω
Resistance @ 50% Max Current:	0.90	Ω
Body Temperature at 100% Max Current:	178.00	°c
Dissipation Constant:	27.0	mw/°c
Thermal Time Constant:	48	Sec.
Material Type (for Beta and Curve):	G	

<b>SL15 40004</b>	
Date: 04/08/2011	Drawn by: Erin Landis
Ametherm, Inc. 3111 N. Deer Run Road Carson City, Nevada USA 89701 www.ametherm.com	Approved By: Mehdi Samii
	Revision: A

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Ametherm:](#)

[SL15 40004](#)