

Front adapters - FLKM 50-PA-MELSEC A1S/32-0 - 2290342

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



VARIOFACE front adapter, for Mitsubishi Electric MELSEC A1S Y81

The figure shows version FLKM 50-PA-MELSEC A1S/32-I

RoHS

Key Commercial Data

Packing unit	5 pc
GTIN	 4 017918 057992
GTIN	4017918057992

Technical data

General

Nominal voltage U_N	24 V AC/DC
Max. permissible current	1 A (per path)
	8 A (per connection, supply via separate power supply)
Mounting position	any

Ambient conditions

Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C

Connection data 1

Connection name	Field level
Connection method	IDC/FLK pin strip
Number of connections	1
Number of positions	50
Pitch	2.54 mm

Standards and Regulations

Standards/regulations	IEC 60664
-----------------------	-----------

Front adapters - FLKM 50-PA-MELSEC A1S/32-0 - 2290342

Technical data

Standards and Regulations

	IEC 60664A
	DIN VDE 0110
	DIN VDE 0160 (in parts)
Degree of pollution	2
Overvoltage category	II

Phoenix Contact 2018 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Phoenix Contact:](#)

[2290342](#)