


- 1

MAXIMUM CONNECTOR INSERTION LOSS IS 0.5dB PLUS CABLE ATTENUATION OF 1.5dB/km AT 1300nm (SEE TABLE)
2.

PRODUCT AND PROCESSING MUST MEET REQUIREMENTS OF TYCO ELECTRONICS STANDARD 230-702



0.56	40.00±0.40	[1574.8±15.8]	4-6435062-0
0.55	35.00±0.35	[1378.0±13.8]	3-6435062-5
0.55	30.00±0.30	[1181.1±11.8]	3-6435062-0
0.54	25.00±0.30	[984.2±11.8]	2-6435062-5
0.53	20.00±0.30	[787.4±11.8]	2-6435062-0
0.52	15.00±0.30	[590.6±11.8]	1-6435062-5
0.52	10.00±0.15	[393.7±5.9]	1-6435062-0
0.51	9.00±0.08	[354.3±3.2]	6435062-9
0.51	8.00±0.08	[315.0±3.2]	6435062-8
0.51	7.00±0.08	[275.6±3.2]	6435062-7
0.51	6.00±0.08	[236.2±3.2]	6435062-6
0.51	5.00±0.08	[196.8±3.2]	6435062-5
0.51	4.00±0.08	[157.5±3.2]	6435062-4
0.50	3.00±0.05	[118.1±2.0]	6435062-3
0.50	2.00±0.05	[78.7±2.0]	6435062-2
0.50	1.00±0.05	[39.4±2.0]	6435062-1
MAX IL (dB)	L METERS [INCHES]		PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN J. W. DAVIS 11OCT05	Tyco Electronics Corporation Harrisburg, PA 17105-3608	
DIMENSIONS: METERS [INCHES]		CHK J. DUNCAN 11OCT05	NAME	
		APVD F. McCORKEL 11OCT05	CABLE ASSEMBLY, FIBER OPTIC, 50/125um, 3.0mm OFNR ZIPCORD SC DUPLEX TO SC DUPLEX, RoHS	
		PRODUCT SPEC	SIZE A2	
		APPLICATION SPEC	CAGE CODE 00779	
MATERIAL -	TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ± - 1 PLC ± - 2 PLC ± - 3 PLC ± - 4 PLC ± - ANGLES ± ± FINISH -	WEIGHT -	DRAWING NO C-6435062	RESTRICTED TO -
CUSTOMER DRAWING			SCALE NTS	SHEET 1 of 1
			REV A	

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[6435062-6](#)