$ \frac{10}{10} + \frac{1}{10} + \frac{1}{10$					3 <u>2</u> 1	
AN       AN <t< th=""><th></th><th></th><th></th><th></th><th></th><th>E DWN A</th></t<>						E DWN A
						arii RK H
$ \frac{1}{12} = \frac{1}{12} + \frac{1}{12}$						
$ \frac{1}{12} = \frac{1}{12} \frac{1}{12$						
$ \frac{1}{12} = \frac{1}{12} \frac{1}{12$						
$ \frac{1}{12} = \frac{1}{12} \frac{1}{12$	YES	71.12[2.800]	28	5-643814-8		
$ \begin{array}{c c c c c c c c c c c c c c c c c c c $						
$ \begin{array}{c c c c c c c c c c c c c c c c c c c $						
$\frac{1}{12} = \frac{1}{12} \left\{ \frac{1}{12} \right\} \right\} \right\} \right\}}{\left\{ \frac{1}{12} \left\{ \frac{1}{12} \left\{ \frac{1}{12} \left\{ \frac{1}{12} \left\{ \frac{1}{12} \right\} \right\} \right\} \right\}} \right\} = \frac{1}{12} \left\{ \frac$						
$\frac{183}{12} 2029(200) = \frac{2}{12}   \frac{1029(12)}{12}   \frac{2}{12}   \frac{1029(12)}{12}   \frac{2}{12}   \frac{1029(12)}{12}   1029(1$						
12       2.3       2.4       2.4       2.4       2.4       2.4       2.4       2.4       2.4       2.5       2.4       2.5       2.						
$ \begin{array}{c} \frac{1}{12} & 1$						
es       4.2/1/ac2       18       4.432 + 2.0         es       4.2/1/ac2       18       4.432 + 2.0         res       4.2/1/ac2       10       4.432 + 2.0         res       4.2/1/ac2       14       4.432 + 2.0         res       3.2/1/ac2       14       4.432 + 2.0         res       3.2/1/ac2       2.4432 + 2.0       1.2/2/ac2       1.2/2/ac2       1.2/2/ac2         res       3.2/2/ac2       2.4432 + 2.0       0.7/2/ac2       1.4/2/ac2       1.4/2/ac2       1.4/2/ac2         res       3.2/2/ac2       2.4432 + 2.0       0.7/2/ac2       1.4/2/ac2       0.7/2/ac2       1.4/2/ac2       0.7/2/ac2       0.7/2/ac2 <t< td=""><td>YES</td><td>50.80[2.000]</td><td>20</td><td>5-643814-0</td><td></td><td></td></t<>	YES	50.80[2.000]	20	5-643814-0		
9.8       2.6.01 L/001       1/2       2.8.4 Set 01 L/001       1/2       <						
11.8       11.6       4.464 SH - 20         12.8       11.6       4.64 SH - 20         12.8       20.2       1.6       4.64 SH - 20         12.8       1.6       4.64 SH - 20       1.6       4.64 SH - 20         12.8       1.6       4.64 SH - 20       1.6       4.6         12.8       1.6       4.64 SH - 20       1.6       4.6         12.8       1.6       4.64 SH - 20       1.6       4.6         12.8       1.6       4.6       4.6       4.6       4.6         12.8       1.6       1.6       4.6       4.6       4.6       4.6         13.8       1.6       1.6       4.6       4.6 <t< td=""><td></td><td></td><td></td><td></td><td><math>\leftarrow 699 \rightarrow 1</math></td><td></td></t<>					$\leftarrow 699 \rightarrow 1$	
118       1					[.275]	
N.9       Assidit A88       IZ       Pression 1445       IZ       Pression 1445       IZ       Pression 1445       Pression 1445 <thp< td=""><td></td><td></td><td></td><td></td><td><math>0.48\pm0.08</math></td><td></td></thp<>					$0.48\pm0.08$	
115       33.02(1/302)       13       4.4424-4.2       4.43141-4.2         115       32.02(1/302)       11       4.443141-2       1.0751       1.0751       1.0564.0024       1.0751       1.0564.0024         115       21.14(402)       8       4.443141-2       1.0751       1.05751       1.0564.0024       1.0751       1.0564.0024       1.0751       1.0564.0024       1.05751       1.0564.0024       1.05751       1.0564.0024       1.05751       1.0564.0024       1.05751       1.0564.0024       1.05751       1.0566.0024	YES	35.56[1.400]				
11:2:00:2:10:0:0:0:0:0:0:0:0:0:0:0:0:0:0					2.54 ±0.05	
132       22.42.0       12.42.43       12.44.31.40       10       14.44.31.40       10       14.44.31.40						
YES       2285 9:00       9       3-73311-9       4.6 / 2.0.08         YES       17.28 (32.21 / 2001)       3 - 743414-9       4.6 / 2.0.08       4.6 / 2.0.08         YES       17.28 (32.21 / 2001)       3 - 743414-9       4.6 / 2.0.08       4.6 / 2.0.08         YES       17.28 (32.21 / 2001)       3 - 743414-9       4.6 / 2.0.08       4.6 / 2.0.08         YES       17.28 (32.21 / 2001)       3 - 743414-9       4.6 / 2.0.08       4.6 / 2.0.08         YES       17.28 (32.21 / 2001)       3 - 743414-9       4.6 / 2.0.08       4.6 / 2.0.08         NC       71.12 / 2.300       2 - 643414-9       1.0.010 IN IN E-64301 - 7       3.68 ± 10.08         NC       8.6 ± 2.000 / 2.001 / 2.01 / 2.1 + 643414 - 5       1.0.010 IN IN E-64301 - 7       3.68 ± 10.028       1.0.2 - 0.01         NC       8.6 ± 2.000 / 2.001 / 2.01 / 2.1 + 643414 - 5       1.0.010 IN IN E-64301 - 7       3.68 ± 10.028       1.0.0201       2.5 + 1.0.021         NC       8.6 ± 2.000 / 2.001 / 2.01 / 2.1 + 643414 - 5       10.010 IN IN E-64301 - 2       10.010 IN IN E-64301 - 2       10.010 IN IN E-64301 - 2         NC       5.0.62 / 2.000 / 2.0 / 2.6 + 2.3 + 14 - 5       10.010 IN E-64301 - 2       10.010 IN IN E-64301 - 2       10.010 IN IN E-64301 - 2         NC       5.0.50 / 2.000 / 2.0 / 2.6 + 2.3 + 14 - 5       10.0000					[.056±.004]	
Yes       20.32 (200)       8       34-735 / -25         Yes       7.22 (200)       6       3-6453 / -25         Yes       7.23 (200)       6       3-6453 / -25         Yes       7.25 (200)       3       3-6453 / -25         Yes       7.25 (200)       2       24453 / -25         Yes       7.25 (200)       2       24454 / -25         Yes       Yes       Yes       Yes </td <td></td> <td></td> <td></td> <td></td> <td></td> <td></td>						
Y-S       Y-APPL COL       Z       A 448/4 4 Z         Y-S       52/10       53       -0.4638 4 - 6         Y-S       52/10       23       -0.4638 4 - 6         Y-S       52/10       23       -0.4638 4 - 6         Y-S       52/10       23       -0.4638 4 - 9         Y-S       50/10       3       -0.4638 4 - 9         Y-S       50/10       2       -0.4638 4 - 9         Y-S       50/10       10       -0.4638 4 - 9         Y-S       2       -0.4638 4 - 9       INFERENCE NALL         Y-S       2       -0.4638 4 - 9       INFERENCE NALL <t< td=""><td></td><td></td><td></td><td></td><td><math>[275][.245]</math> <math>4.67\pm0.08</math> <math>[A]A[A]A]</math></td><td></td></t<>					$[275][.245]$ $4.67\pm0.08$ $[A]A[A]A]$	
123       12.74 (2.3)       0	YES					
M.S.       Div. [2.40]       4       3       A = A 5944.4       A       A       A = A 5944.4       A						
123       0.18.1420       1       1.92.341-3         123       7.63.200       2       3-643814-3       1.5.21         125       7.63.200       2       3-643814-3       1.5.21         125       1.5.220       1.5.21       1.5.21       1.5.21         125       2.63.200       2       3-643814-3       1.5.21       1.5.21         126       2.1002       2       3-643814-3       1.5.21       1.5.20         126       2.1002       2       2.643814-3       1.5.20       1.5.20         126       2.1002       2.52       2.643814-3       1.5.20       1.5.20         126       2.1002       2.52       2.643814-3       1.5.20       1.5.20         127       2.522       2.643814-3       2.5441-3       1.5.21       1.5.20         127       2.522       2.643814-3       2.5441-3       2.5441-3       2.5441-3         127       2.222       2.64381-4       2.54514-3       2.54514-3       2.54514-3         127       2.223       2.22       2.64381-3       2.55514-3       2.55514-3       2.55514-3         128       1.5451-350       1.5451-3       1.5551-3       2.55514-3       2.55514-3					_3.66±0.08	
YTS       5.06[-00]       2       3-643814-2       (5.20]       3         C       71.19(2403)       28       28.43814-2       Superstand       (5.20]       (5.20)         C       71.19(2403)       28       28.43814-2       Superstand       (5.20)					$[.144\pm.003]$	
Y0       47.12[2:900       28       2.51441-8       Superscript v: 5.6381.4-8         Y0       68.65/7.000       27       2-64.8314-6       Superscript v: 5.64.814-6         Y0       66.65/7.400       28       2.64.3314-7       Superscript v: 5.64.814-6         Y0       65.69/7.400       24       2-64.3814-7       Superscript v: 5.64.814-6         Y0       55.69/7.400       22       2-64.3814-7       Superscript v: 5.64.3814-7         Y0       55.69/7.400       27       2-64.3814-7       Superscript v: 5.64.3814-7         Y0       55.49/7.200       22       2-64.3814-7       Superscript v: 5.64.3814-7         Y0       55.38/7.200       22       2-64.3814-7       Superscript v: 5.64.3814-7         Y0       55.38/7.200       19       2-64.3814-7       Superscript v: 5.64.3814-7         Y0       45.77(1.800       13       2-64.3814-7       Superscript v: 6.64.3814-7         Y0       45.77(1.800       16       16.43.814-8       WITCH       2.52.06.00         Y0       45.79(1.800       14       16.43.814-7       Superscript v: 6.43.814-7         Y0       35.581/400       14       16.43.814-8       Superscript v: 6.43.814-7         Y0       35.581/400       14					$\top \cup \cdot \angle$	
NO       66.55       2.70       2.43814 - 5       X = 44814 - 7 / X = 43814 - 5 / X = 4381						
NO       63.55 <sup>1</sup> /2.501       29       2+44.844-4       XI         NO       60.85 <sup>1</sup> /2.400       24       2-64.3514-4       SUPERSEDED by 5-64.3814-4/A         NO       55.85 <sup>1</sup> /2.200       23       2-64.3514-4       SUPERSEDED by 5-64.3814-4/A         NO       55.85 <sup>1</sup> /2.200       27       2-64.3514-4       SUPERSEDED by 5-64.3814-4/A         NO       55.85 <sup>1</sup> /2.200       27       2-64.3514-4       SUPERSEDED by 5-64.3814-4/A         NO       55.85 <sup>1</sup> /2.200       20       2-64.3514-4       SUPERSEDED by 5-64.3814-4/A         NO       55.85 <sup>1</sup> /2.200       20       2-64.3514-4       SUPERSEDED by 5-64.3814-4/A         NO       56.85 <sup>1</sup> /2.200       20       2-64.3514-4       SUPERSEDED by 5-64.3814-4/A         NO       45.15 <sup>1</sup> /2.1800       18       1-64.3814-9       SUPERSEDED by 4-64.3814-9         NO       45.15 <sup>1</sup> /2.1800       18       1-64.3814-4       SUPERSEDED by 4-64.3814-7/A         NO       45.15 <sup>1</sup> /2.1800       16       1-64.3814-4       SUPERSEDED by 4-64.3814-7/A         NO       33.02 <sup>1</sup> /2.001       17       1-64.3814-4       SUPERSEDED by Control MA         NO       35.05 <sup>1</sup> /2.000       10       1-64.3814-4       SUPERSEDED by Control MA         NO       25.25 <sup>1</sup> /2.0	NO	68.58[2.700]	27			
Inc.       Gold 2:00       22       2:00					$\frac{1}{1} \text{ material } \text{ connector } = \text{ nylon } 194\text{ v} = 2 \text{ (white)}$	
NO       58.42[2:300       23       2-8438/4-2       Surrssubb BY 5-6438/4-2         NO       55.88[2:200       22       2-8438/4-2       Surrssubb BY 5-6438/4-2         NO       55.88[2:200       22       2-8438/4-2       Surrssubb BY 5-6438/4-2         NO       55.88[2:200       20       2-8438/4-2       Surrssubb BY 5-6438/4-2         NO       55.88[2:200       20       2-8438/4-2       Surrssubb BY 5-6438/4-2         NO       55.88[2:200       20       2-8438/4-2       Surrssubb BY 5-6438/4-2         NO       45.72[1:200]       19       4-6438/4-2       Surrssubb BY 5-6438/4-2         NO       45.72[1:200]       18       1-8435/4-5       Surrssubb BY 5-6438/4-7         NO       45.72[1:200]       18       1-8438/4-7       Surrssubb BY 5-6438/4-7         NO       45.72[1:200]       15       1-6438/4-7       Surrssubb BY 5-6438/4-7         NO       35.02[1:300]       16       1-6438/4-7       Surrss					CONTACTS 0.30[012] THICK CODDED ALLOY	
NO       55.88[2:00]       22       2-643814-2       Superscool by 5-643814-2         NO       55.36[2:00]       20       2-643814-3       Superscool by 5-643814-1         NO       45.72[1:800]       19       -643814-3       Superscool by 4-643814-2         NO       45.72[1:800]       19       -643814-3       Superscool by 4-643814-3         NO       45.72[1:800]       16       1-643814-4       Superscool by 4-643814-7         NO       45.72[1:800]       16       1-643814-5         NO       45.72[1:800]       16       1-643814-5         NO       45.72[1:800]       16       1-643814-5         NO       35.56[1:400]       14       1-643814-5         NO       35.56[1:400]       14       1-643814-5         NO       35.56[1:400]       12       1-643814-5         NO       35.56[1:400]       12       1-643814-5         NO       35.56[1:400]       11       1-643814-5         NO       35.56[1:400]       12       1-643814-5         NO       25.46[1:000]       12       1-643814-5         NO       25.46[1:000]       10       1-643814-5         NO       25.46[1:000]       16       643814-5 </td <td></td> <td></td> <td></td> <td></td> <td>BRIGHT TIN-LEAD .00203[.000080] MIN THICKNESS</td> <td></td>					BRIGHT TIN-LEAD .00203[.000080] MIN THICKNESS	
NO       53.34[2.100]       21       2.643814 - 1       SUPERSEDED BY 5.643814 - 1         NO       50.80[2.000]       20       2-643814 - 0       SUPERSEDED BY 4.643814 - 9]         NO       48.28[1.900]       18       1-643814 - 2       SUPERSEDED BY 4.643814 - 9]         NO       48.28[1.900]       18       1-643814 - 8       SUPERSEDED BY 4.643814 - 9]         NO       43.18[1.700]       17       1-643814 - 8       SUPERSEDED BY 4.643814 - 9]         NO       43.18[1.700]       16       1-643814 - 8       SUPERSEDED BY 4.643814 - 9]         NO       38.10[1.500]       15       1-643814 - 5       SUPERSEDED BY 4.643814 - 7]         NO       35.56[1.400]       14       1-643814 - 2       SUPERSEDED BY 4.643814 - 7]         NO       35.56[1.400]       14       1-643814 - 2       SUPERSEDED BY 4.643814 - 7]         NO       35.56[1.400]       14       1-643814 - 2       SUPERSEDED BY 4.643814 - 2         NO       25.40[1.100]       11       1-643814 - 2       SUPERSEDED BY 4.643814 - 2         NO       27.94[1.100]       11       1-643814 - 2       SUPERSEDED BY 4.643814 - 2         NO       27.94[1.100]       11       1-643814 - 2       SUPERSEDED BY 4.643814 - 2         NO <td< td=""><td></td><td></td><td></td><td></td><td>FUR 043014 - 2 IHRU 2 - 043014 - 0.</td><td></td></td<>					FUR 043014 - 2 IHRU 2 - 043014 - 0.	
NO       48.26[1.900]       19       1-643814-9       XUPERSEDED BY 4-643814-9         NO       45.72[1.800]       18       1-643814-7       SUPERSEDED BY 4-643814-7         NO       45.18[1.700]       17       1-643814-7       SUPERSEDED BY 4-643814-7         NO       45.18[1.700]       16       1-643814-7       SUPERSEDED BY 4-643814-7         NO       35.56[1.400]       14       1-643814-3         NO       35.56[1.400]       14       1-643814-3         NO       30.02[1.300]       13       1-643814-3         NO       30.48[1.200]       12       1-643814-3         NO       22.940[1.100]       11       1-643814-3         NO       22.940[1.000]       10       1-643814-3         NO       22.940[1.000]       10       1-643814-3         NO       22.940[1.000]       10       1-643814-3         NO       22.940[1.000]       6       643814-8         NO       17.78[.700]       7       643814-7         NO       17.24[.600]       6       643814-6         NO       12.70[.500]       5       643814-6         NO       12.72[.500]       5       643814-6         NO       <	NO	53.34[2.100]			MATE WHISTER WHIGHED THE OUZOJ.000000 WIN THERNESS	
NG       45.72[1.800]       18       1-643814-8         NC       43.18[1.700]       17       1-643814-6         NG       43.18[1.700]       16       1-643814-5         NG       36.10[1.500]       15       1-643814-5         NG       35.56[1.400]       14       1-643814-6         NG       30.48[1.200]       13       1-643814-3         NG       30.48[1.200]       12       1-643814-1         NG       27.94[1.100]       11       1-643814-2         NG       27.94[1.100]       10       1-643814-3         NG       25.40[1.000]       10       1-643814-7         NG       22.68[.900]       9       643814 -8         NG       17.78[.700]       7       643814 -4         NG       17.78[.700]       7       643814 -5         NG       17.27[.500]       6       643814 -5         NG       17.27[.500]       6       643814 -5         NG       17.27[.500]       6       643814 -5         NG       17.27[.500]       5       643814 -5         NG       17.27[.500]       6       643814 -5         NG       17.27[.500]       6       643814 -5						
NC       43.18[1.700]       17       1-643814-7       SUPERSEDED BY 4-643814-7]         NC       40.64[1.600]       16       1-643814-6         NC       35.56[1.400]       14       1-643814-6         NC       35.56[1.400]       14       1-643814-7         NC       33.02[1.300]       13       1-643814-7         NC       30.48[1.200]       12       1-643814-7         NC       25.40[1.000]       10       1-643814-7         NC       25.40[1.000]       10       1-643814-7         NC       22.86[390]       9       643814-7         NC       22.86[390]       9       643814-7         NC       15.24[600]       6					INSULATION DIAMETER.	
NO       40.64[1.600]       16       1-643814-6         NO       38.10[1.500]       15       1-643814-5         NO       35.56[1.400]       14       1-643814-4         NO       35.02[1.300]       13       1-643814-2         NO       30.48[1.200]       12       1-643814-2         NO       27.94[1.100]       11       1-643814-1         NO       27.94[1.100]       11       1-643814-2         NO       27.94[1.100]       10       1-643814-4         NO       22.40[1.000]       10       1-643814-7         NO       20.32[.800]       8       643814-7         NO       17.78[.700]       7       643814-7         NO       15.24[.600]       6       643814-7         NO       12.70[.500]       5       643814-5         NO       12.70[.500]       5       643814-5         NO       10.16[.400]       4       643814-5         NO       12.70[.500]       5       643814-5         NO       10.16[.400]       4       643814-4         NO       7.62[.300]       3       643814-3					JERSEDED BY 4-643814-7 A 3. CONTACTS MUST ACCEPT 0.64±0.03[.025	
NO       38.10[1.500]       15       1-643814-5         NC       35.56[1.400]       14       1-643814-4         NC       33.02[1.300]       13       1-643814-3         NC       30.48[1.200]       12       1-643814-1         NC       27.94[1.100]       11       1-643814-1         NC       25.40[1.000]       10       1       1-643814-9         NC       22.86[.900]       9       643814-9         NC       22.86[.900]       9       643814-7         NC       17.78[.700]       7       643814-7         NC       15.24[.600]       6       643814-7         NC       12.70[.500]       5       643814-7         NC       7.62[.300]       3       643814-7         NC       7.62[.300]       3       643814-7					$\wedge$	
NO       33.05 [1.400]       14       I-643814-4         NO       33.02[1.300]       13       1-643814-3         NO       30.48[1.200]       12       1-643814-2         NO       27.94[1.100]       11       1-643814-0         NO       22.86[.900]       9       643814-9         NO       22.86[.900]       9       643814-8         NO       17.78[.700]       7       643814-5         NO       15.24[.600]       6       643814-5         NO       15.24[.600]       6       643814-5         NO       15.24[.600]       6       643814-5         NO       10.16[.400]       4       643814-5         NO       10.270[.500]       5       643814-5         NO       10.16[.400]       4       643814-4         NO       7.62[.300]       3       643814-3		38.10[1.500]			4 IDENTIFICATION NUMBER FOR LAST CIRCUIT MAY	
NO       30.48[.200]       12       1-643814-2         NO       27.94[1.100]       11       1-643814-1         NO       25.40[1.000]       10       1-643814-9         NO       22.86[.900]       9       643814-9         NO       20.32[.800]       8       643814-8         NO       17.78[.700]       7       643814-7         NO       15.24[.600]       6       643814-7         NO       12.70[.500]       5       643814-5         NO       12.70[.500]       6       643814-4         NO       12.70[.500]       5       643814-4         NO       7.62[.300]       3       643814-3						
NO       27.94[1.100]       11       1-643814-1         NO       25.40[1.000]       10       1-643814-0         NO       22.86[.900]       9       643814-9         NO       20.32[.800]       8       643814-7         NO       17.78[.700]       7       643814-6         NO       15.24[.600]       6       643814-6         NO       12.70[.500]       5       643814-5         NO       10.16[.400]       4       643814-4         NO       7.62[.300]       3       643814-4						
NO       25.40[1.000]       10       1-643814-0         NO       22.86[.900]       9       643814-9         NO       20.32[.800]       8       643814-7         NO       17.78[.700]       7       643814-6         NO       15.24[.600]       6       643814-5         NO       12.70[.500]       5       643814-4         NO       12.70[.500]       5       643814-4         NO       7.62[.300]       3       643814-4					6. HOUSING FEATURES ARE: CLOSED END WITH LOCKING RAMP AND WITH POLARIZING TAR	
NO       22.86[.900]       9       643814 - 9         NO       20.32[.800]       8       643814 - 8         NO       17.78[.700]       7       643814 - 7         NO       15.24[.600]       6       643814 - 6         NO       12.70[.500]       5       643814 - 5         NO       10.16[.400]       4       643814 - 4         NO       7.62[.300]       3       643814 - 3					$\wedge$	
NO       17.78[.700]       7       643814 - 7         NO       15.24[.600]       6       643814 - 6         NO       15.24[.600]       6       643814 - 6         NO       12.70[.500]       5       643814 - 5         NO       12.70[.500]       5       643814 - 5         NO       10.16[.400]       4       643814 - 4         NO       7.62[.300]       3       643814 - 3					PER D.RENAUD/D.SINISI	
NO       17.78[.700]       7       643814 - 7         NO       15.24[.600]       6       643814 - 6         NO       15.24[.600]       6       643814 - 6         NO       12.70[.500]       5       643814 - 5         NO       12.70[.500]       5       643814 - 5         NO       10.16[.400]       4       643814 - 4         NO       7.62[.300]       3       643814 - 3	NO	20.32[.800]	8		THIS DRAWING IS A CONTROLLED DOCUMENT.	otivity
NO       12.70[.500]       5       643814 - 5         NO       10.16[.400]       4       643814 - 4         NO       7.62[.300]       3       643814 - 3						cuvity
NO       12.70[.500]       5       643814-5         NO       10.16[.400]       4       643814-4         NO       7.62[.300]       3       643814-3       24 AWG, STANDARD					mm [INCHES]  MTA-100 CONNECTOR ASSEME	BLY,
NO 7.62[.300] 3 643814-3 NO 7.62[.300] 3 643814-3 NO RES					1 PLC ± PRODUCT SPEC 24 AWG. STANDARD	
NO $5.08[.200]$ 2 $643814-2$			•		A C C C C C C C C C C C C C C C C C C C	RESTRICT
		5.08[.200]			$\begin{bmatrix} ANGLES \pm 114-1019 \\ AZ 00779 C-643814 \end{bmatrix}$	

1471-9 (3/11)

2D

	THIS DRAWING IS A CO	ONTROLLED DOCUMENT.	DWN 11JUN2003 S. CARPENTER CHK 11JUN2003	TE Connectivity
]		TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ± 1 PLC ± 2 PLC ± 3 PLC ± 0.13 [.005]	D. BOSSI APVD 11JUN2003 D. BOSSI PRODUCT SPEC 108-1050 APPLICATION SPEC	MTA-100 CONNECTOR ASSEMBLY, 24 AWG, STANDARD
21C		4 PLC ± ANGLES ± FINISH	114-1019 weight	A 2 00779 C=643814
			CUSTOMER DRAWING	SCALE 5.1 SHEET 1 OF 1 REV J2

## **Mouser Electronics**

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

TE Connectivity: 3-643814-5