



0.25 MAX CUT-OFF

DIM E REF

Y

T

T

Y

5

DIM C

DIM D REF

SECTION T-T

SCALE 20:1

DIM A

DIM B REF

SECTION Y-Y

SCALE 20:1

18.24	2.40	2.60 2.20	1.55	1.96 1.57	1.30 - 1.60	22-24 AWG	ON REEL	6	3-2106124-3
18.24	2.40	2.60 2.20	1.55	1.96 1.57	1.30 - 1.60	22-24 AWG	LOOSE PIECE	2 3	2-2106124-7
18.24	2.40	2.60 2.20	1.55	1.96 1.57	1.30 - 1.60	22-24 AWG	ON REEL	2 3 4	2-2106124-3
18.24	2.40	2.60 2.20	1.55	1.96 1.57	1.30 - 1.60	22-24 AWG	ON REEL	2 3	2-2106124-2
18.24	3.01	2.80 2.40	2.05	2.32 1.92	1.70 - 2.10	18-20 AWG	LOOSE PIECE	2 3	2106124-9
18.24	3.01	2.80 2.40	2.05	2.32 1.92	1.70 - 2.10	18-20 AWG	ON REEL	2 3 4	2106124-3
18.24	3.01	2.80 2.40	2.05	2.32 1.92	1.70 - 2.10	18-20 AWG	ON REEL	2 3	2106124-2
DIM E	DIM D	DIM C	DIM B	DIM A	INSULATION DIA	WIRE RANGE	REMARKS	FINISH	PART NO

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN R BROWN 05MAR2009

CHK A BUCHER 05MAR2009

APVD -

PRODUCT SPEC 108-2391

APPLICATION SPEC 114-13261

WEIGHT -

CUSTOMER DRAWING

DIMENSIONS: mm

TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ± 1 PLC ±0.13 2 PLC ± 3 PLC ± 4 PLC ANGLES ±1° FINISH

SEE NOTES

TE Connectivity

CONTACT, TAB, CRIMP SNAP-IN SLIM SEAL SSL

SIZE A2

CAGE CODE 00779

DRAWING NO C-2106124

RESTRICTED TO -

SCALE 10:1

SHEET 1 OF 1

REV A5

1471-9 (3/11)

Pro/ENGINEER DRAWING

1

2

3

4

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[2-2106124-2](#)