

THIS DRAWING IS UNPUBLISHED.
VERTRAULICHE UNVERÖFFENTLICHTE ZEICHNUNG

RELEASED FOR PUBLICATION
FREI FÜR VERÖFFENTLICHUNG

ALL RIGHTS RESERVED.
ALLE RECHTE VORBEHALTEN

© COPYRIGHT - By -

REVISIONS
ÄNDERUNGEN

P	LTR	DESCRIPTION BESCHREIBUNG	DATE	DWN	APVD
	C7	REVISED PER ECR-17-014951	16OCT2017	BDA	KR

3.9

1.65

5.08

5.08

4.7

20.3

1

2

3

4

5

6

926682

XXXX

27.4

14

2.5

7

8.2

25.9

11.2

11

Montageausschnitt / PANEL CUT OUT
Bestückungsseite / LOADING SIDE
M 2:1 / SCALE 2:1

14.35±0.13

4.45±0.25

12.19±0.25

2.79±0.13

2.54±0.25

6.35±0.25

6.99±0.25

26.16±0.13

4.45±0.25

4

5

1

2

3

4

5

6

7

8

9

10

11

12

Bemerkungen:
NOTES

1

Geeignet für UMNL Stift- und Buchsenkontakte
BEEN SUITABLE FOR UMNL PIN- AND SOCKET CONTACTS

2

Empfohlene Blechstärke 0.75 – 2.3 mm
RECOMMEND SHEET METAL THICKNESS 0.75 – 2.3 mm

3

Gehäuse muß in Stanzrichtung eingeführt werden
HOUSING MUST BE INTRODUCED TO PUNCHING DIRECTION

4

Für verschlüsseltes Einsetzen der Gehäuse
FOR CODED USING OF THE HOUSING

5

Position von Kammer 1 bei Verschlüsselterm Einsetzen
POSITION OF CAVITY 1 FOR CODED USING

6

Neues Material (Phosphor und Halogen frei)
NEW MATERIAL (PHOSPHORUS AND HALOGENEOUS FREE)

7

Hersteller-Logo und Ländercode nach TE-SPEZ. 115-18016
BRANDNAME AND MANUFACTURING LOCATION CODE ACCORDING TE-SPEC. 115-18016

8

MATERIAL CORRESPONDING TO THE REQUIRMENT OF IEC 60335-1
(INCL. GLOW WIRE TEST 750°C WITH OUT FLAME)

9

PRELIMINARY PART NOT RELEASED FOR PRODUCTION

10

MATERIAL P/N: 702641-1.

11

CSA LOGO LOCATED AT LEAST ONE SIDE
OF THE HOUSING, LOCATED AS SHOWN

12

DIMENSIONS SHOWN REPRESENT PRODUCT IN DRY, AS MOLDED,
CONDITION. ADDITIONAL 2% GROWTH DUE TO SUBSEQUENT MOISTURE
ABSORPTION MAY OCCUR AND SHOULD BE ACCOUNTED FOR.

926682-7

1

PA6.UL94 V 0

8

9

natur/NATURAL

OBSOLETE

~~926682-6~~

C

PA6.6 UL94 V 2 (ZYTEL E 103 HSL)

natur/NATURAL

OBSOLETE

~~926682-5~~

C

PA6.6 UL94 V 2 (ZYTEL ...135F)

natur/NATURAL

926682-4

C

PA6.6 UL94 V 2 (ZYTEL ...135F)

10

weiß/WHITE

926682-3

C

PA6.6 UL94 V 0 (ULTRAMID C3U)

6

natur/NATURAL

OBSOLETE

~~926682-2~~

C

PA6.6 UL94 V 2 (ZYTEL ...135F)

schwarz/BLACK

926682-1

C

PA6.6 UL94 V 2 (ZYTEL E 101)

natur/NATURAL

PART NO

REV.

MATERIAL

COLOR

THIS DRAWING IS A CONTROLLED DOCUMENT.
DIESE ZEICHNUNG IST EIN KONTROLLIERTES DOKUMENT.

DIMENSIONS:
MASSENGHEITEN
mm

1

2

3

4

PLC ± -

PLC ± -

PLC ± -

PLC ± -

ANGLES / WINKEL ± -

FINISH / OBERFLÄCHE / FARBE

TOLERANCES UNLESS
OTHERWISE SPECIFIED:
± 0.13 mm
± 0.25 mm
± 0.13 mm
± 0.13 mm

8

1

2

3

4

PLC ± -

PLC ± -

PLC ± -

PLC ± -

ANGLES / WINKEL ± -

FINISH / OBERFLÄCHE / FARBE

DWN
Abraham, G.

11-MAR-03

CHK
Kampmann, H.

12-MAR-03

APVD
-

-

PRODUCT SPEC
PRODUKTSPEZ
108-1031

APPLICATION SPEC
VERARBEITUNGSSPEZ
114-18011

WEIGHT
GEWICHT
0,000000

CUSTOMER DRAWING / KUNDENZEICHNUNG

NAME

6-pol. UMNL Aufnahmegehäuse
UMNL 6-WAY CAP HOUSING

SIZE
A2

CAGE CODE
00779

DRAWING NO
ZEICHNUNGS-NR.
C=926682

RESTRICTED TO
NUR FÜR
-

1471-9 (1/15)

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[926682-1](#)