

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

OCT. 2005

© COPYRIGHT 2005

BY -

ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	A1	Released as per ECR-08-022292	4-Sep-08	SP	JC
	AH	ECR-16-003725	12MAR2016	KR	TN

LASER MARKING: TE LOGO PN VALUE  
TOLERANCE & DATE CODE4 HOLES OF  $\varnothing 4.4$ 

1 FOR FURTHER INFORMATION SEE DATA SHEET FOR  
HS SERIES-ALUMINIUM HOUSED RESISTORS2 FOR A SPECIFIC PN FOR A RESISTANCE VALUE  
AND TOLERANCE, PLEASE REFER TO DMF

3 TECHNICAL SPECIFICATION

DISSIPATION AT 25°C : 100 WATTS MOUNTED  
ON STD HEATSINK

OHMIC RANGE : R10 TO 75K

STABILITY :  $\Delta R < = 2\%$  PER 1000Hrs

ISOLATION VOLTAGE : 3500V DC/AC pk

MAX WORKING VOLTAGE : 1900V DC/AC rms

TEMP COEFFICIENT : > 1R0 50ppm  
> 100R 25ppm

CLIMATIC CATEGORY : 55/200/56

RoHS Compliant

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN 27.SEP.05  
DAVE KENNEDYCHK 28.SEP.05  
J CATCHPOLEAPVD 28.SEP.05  
J CATCHPOLE

PRODUCT SPEC

APPLICATION SPEC

WEIGHT -

CUSTOMER DRAWING

DIMENSIONS:

mm

TOLERANCES UNLESS  
OTHERWISE SPECIFIED:

0 PLC	$\pm 0.5$
1 PLC	$\pm 0.2$
2 PLC	$\pm 0.1$
3 PLC	$\pm$
4 PLC	$\pm$
ANGLES	$\pm 5^\circ$

MATERIAL

material\_2

FINISH

finish\_spec\_2

TE Connectivity

NAME  
HSC100 METAL HOUSED  
POWER RESISTOR

SIZE CAGE CODE DRAWING NO

A3 00779 C=1625999

RESTRICTED TO

-

SCALE 1:1

SHEET 1 OF 1

REV AH

1470-19 (3/13)

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[HSC10075RJ](#)