



47200 in use (<u>47204</u> Ground cord sold separately)



47201 in use





Made in the United States of America

SPECIFICATIONS

- Ideal for working on heavier assemblies in an EPA
- ESD protective for use with ESD sensitive assemblies
- Durable 1/4" (6mm) thick Dissipative, Crosslink Polyethylene Foam
- Galvanized Steel Turntable located at the bottom
- Size: Choice of 12-1/2" (318mm) or 15-1/2" (394mm) Octagon (across flats)
- Very low profile both sizes only 1" (25mm) high
- Weight capacity 50 lbs (23 Kg)
- Volume Resistance 1 x 10⁶ to < 1 x 10⁹ ohms per ANSI/STM11.12
- Meets worksurface require limit of ANSI/ESD S20.20 per ANSI/ESD S541 and ESD TR53
- Electrostatic charges removed to ground via contact on grounded ESD worksurface or via ground cord from ring terminal
- Made in the United States of America

Item	Size (Octagon across flats)
<u>47200</u>	12-1/2" (318mm)
<u>47201</u>	15-1/2" (394mm)



Galvanized Steel Turntable

Unless specified tolerance is ±10%

Specifications and procedures subject to change without notice.

ESD DISSIPATIVE TURNTABLE

PROTEKTIVE PAK

PROTEKTIVE PAK

13520 MONTE VISTA AVENUE, CHINO, CA 91710 PHONE (909) 627-2578

ProtektivePak.com

DRAWING NUMBER 47200 June 2016

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Protektive Pak: 47201 47200