





8	7	6	1,2,39,40	1,2,39,40	3.984	3.900	39	80	7-104354-0
	7	6	1,2,29,30	1,2,29,30	2.984	2.900	29	60	6-104354-9
	7	6	1,2,24,25	1,2,24,25	2.484	2.400	24	50	6-104354-8
	7	6	1,2,19,20	1,2,19,20	1.984	1.900	19	40	6-104354-7
	7	6	1,2,16,17	1,2,16,17	1.684	1.600	16	34	6-104354-6
	7	6	1,2,14,15	1,2,14,15	1.484	1.400	14	30	6-104354-5
	7	6	1,2,13,14	1,2,13,14	1.384	1.300	13	28	6-104354-4
	7	6	1,2,12,13	1,2,12,13	1.284	1.200	12	26	6-104354-3
	7	6	1,2,11,12	1,2,11,12	1.184	1.100	11	24	6-104354-2
	7	6	1,2,10,11	1,2,10,11	1.084	1.000	10	22	6-104354-1
	7	6	1,2,9,10	1,2,9,10	.984	.900	9	20	6-104354-0
	7	6	1,2,8,9	1,2,8,9	.884	.800	8	18	5-104354-9
	7	6	1,2,7,8	1,2,7,8	.784	.700	7	16	5-104354-8
	7	6	1,2,6,7	1,2,6,7	.684	.600	6	14	5-104354-7
	7	6	1,2,5,6	1,2,5,6	.584	.500	5	12	5-104354-6
7	6	1,2,4,5	1,2,4,5	.484	.400	4	10	5-104354-5	
7	6	1,2,3,4	1,2,3,4	.384	.300	3	8	5-104354-4	
7	6	1,2,3	1,2,3	.284	.200	2	6	5-104354-3	
7	6	1,2	1,2	.184	.100	1	4	5-104354-2	
8	5	5	1,2,39,40	1,2,39,40	3.984	3.900	39	80	2-104354-0
8	5	5	1,2,29,30	1,2,29,30	2.984	2.900	29	60	1-104354-9
8	5	5	1,2,24,25	1,2,24,25	2.484	2.400	24	50	1-104354-8
8	5	5	1,2,19,20	1,2,19,20	1.984	1.900	19	40	1-104354-7
8	5	5	1,2,16,17	1,2,16,17	1.684	1.600	16	34	1-104354-6
8	5	5	1,2,14,15	1,2,14,15	1.484	1.400	14	30	1-104354-5
8	5	5	1,2,13,14	1,2,13,14	1.384	1.300	13	28	1-104354-4
8	5	5	1,2,12,13	1,2,12,13	1.284	1.200	12	26	1-104354-3
8	5	5	1,2,11,12	1,2,11,12	1.184	1.100	11	24	1-104354-2
8	5	5	1,2,10,11	1,2,10,11	1.084	1.000	10	22	1-104354-1
8	5	5	1,2,9,10	1,2,9,10	.984	.900	9	20	1-104354-0
8	5	5	1,2,8,9	1,2,8,9	.884	.800	8	18	104354-9
8	5	5	1,2,7,8	1,2,7,8	.784	.700	7	16	104354-8
8	5	5	1,2,6,7	1,2,6,7	.684	.600	6	14	104354-7
8	5	5	1,2,5,6	1,2,5,6	.584	.500	5	12	104354-6
8	5	5	1,2,4,5	1,2,4,5	.484	.400	4	10	104354-5
8	5	5	1,2,3,4	1,2,3,4	.384	.300	3	8	104354-4
8	5	5	1,2,3	1,2,3	.284	.200	2	6	104354-3
8	5	5	1,2	1,2	.184	.100	1	4	104354-2
8	5	5	1	1	.084	—	—	2	104354-1
	REMARKS	PLATING	ROW N	ROW M	C	B	A	NO OF POSN	ASSEMBLY PART NUMBER
			HOLD-DOWN POST CONFIG LOCATION						

THIS DRAWING IS A CONTROLLED DOCUMENT.						DIN M. PASTAL 2-4-88 OK R. FEIDT 2-9-88		 TE Connectivity	
DIMENSIONS:		TOLERANCES UNLESS OTHERWISE SPECIFIED:		APPROVED R. FEIDT 2-9-88		NAME _____			
INCHES				PRODUCT SPEC		HEADER ASSEMBLY, MOD II, BREAKAWAY, RIGHT ANGLE, DOUBLE, ROW, .100X.100 CL, .025 SQ POSITS WITH HOLD-DOWN CONFIGURATIONS			
		0 PL ± — 1 PL ± — 2 PL ± — 3 PL ± .005 4 PL ± — ANGLES ± —		APPLICATION SPEC		SIZE CAGE CODE DRAWING NO		RESTRICTED TO	
MATERIAL: HYDRA-METAL FLAME RETARDANT THERMOPLASTIC POLYIMIDE POSTS: COPPER ALLOY		FINISH SEE TABLE		WEIGHT —		A1 00779 C=104354		—	
CUSTOMER DRAWING						SCALE 4:1		SHEET 1 OF 1 REV H	

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[104354-3](#)