



*Quality Products. Service Excellence.*

## Type 1 Mild Steel Splitter Box *CSB Series*

Hinged Door with Screw



### Application

- The splitter boxes are designed for indoor distribution of up to 600 A (max) service using either 3 or 4 wires. 75° C conductor ampacity permitted.

### Standards

- CSA Type 1
- Complies with
  - IEC 60529, IP20

### Construction

- Formed and spot welded from 14 or 16 gauge steel.
- Factory installed splitter blocks - 3 or 4 wire option. Empty box without splitter blocks also offered.
- Series of knockouts on each side.
- Padlocking hasp.

### Finish

- Enclosure and cover are finished in ANSI 61 gray powder coating.

### Accessories

- Splitter Blocks
- Grounding Kits

**New and improved PDF part drawing files with more detail now available.**

Click part number in table below to access PDF, DXF, and STEP files.

| 3 Wire<br>Part No. | 4 Wire<br>Part No. | Less Blocks<br>Part No. | CU/AL<br>Amps | H     | Enclosure<br>W | D    |
|--------------------|--------------------|-------------------------|---------------|-------|----------------|------|
| CSB73              | CSB74              | CSB70                   | 70/70         | 12.00 | 10.00          | 4.00 |
| CSB103             | CSB104             | CSB100                  | 125/120       | 15.00 | 10.00          | 4.00 |
| CSB203             | CSB204             | CSB200                  | 225/180       | 18.00 | 12.00          | 5.00 |
| CSB403             | CSB404             | CSB400                  | 400/400       | 24.00 | 17.00          | 6.00 |
| CSB603*            | CSB604*            | CSB600*                 | 600/600       | 30.00 | 24.00          | 7.00 |

\* 14 gauge steel

*Data subject to change without notice*



# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Hammond:](#)

[CSB100](#) [CSB70](#) [CSB203](#) [CSB404](#) [CSB600](#) [CSB603](#) [CSB103](#) [CSB200](#) [CSB104](#) [CSB73](#) [CSB74](#) [CSB604](#)  
[CSB403](#) [CSB204](#) [CSB400](#)