



Product: <u>8920</u> ☑

Lead Wire, #22 Str TC, PVC Ins, AWM 1015 CSA TYPE TEW

Request Sample

Product Description

Low Temp Plastic Lead Wire, 22AWG (7x30) Tinned Copper, PVC Insulation, AWM 1015 CSA TYPE TEW JQA-F 600V 105C

Technical Specifications

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Material	No. of Conductors
22	7x30	TC - Tinned Copper	1
Condu	ctor Count:	1	

Insulation

Mate	rial	Nominal Diameter	Nominal Wall Thickness
PVC - Polyvi	nyl Chloride	0.093 in	0.03 in

Electrical Characteristics

Voltage

Non-UL Voltage Rating	UL Voltage Rating
600 V	600 V

Temperature Range

Non-UL Temp Rating:	105°C
UL Temp Rating:	105°C

Mechanical Characteristics

Bulk Cable Weight:

Standards

UL AWM Style:	MTW or AWM 1015/1230
CSA Rating:	600 V, 105°C
CSA AWM Specification:	AWM I A/B or TEW
CSA Type:	AWM I A/B or TEW
Military Specification:	N/A

Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes

EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-07-01
MII Order #39 (China RoHS):	Yes

Flammability, LS0H, Toxicity Testing

UL Flammability:	VW-1
CSA Flammability:	FT1
UL voltage rating:	600 V RMS

Plenum/Non-Plenum

Plenum (Y/N):	No		

Part Number

Variants

Item #	Color	UPC	Length	Footnote
8920 010100	Black	612825220688	100 ft	
8920 0101000	Black	612825220695	1,000 ft	Р
8920 0105000	Black	612825220701	5,000 ft	С
8920 013100	Blue, Dark	612825220732	100 ft	
8920 0131000	Blue, Dark	612825220749	1,000 ft	Р
8920 0011000	Brown	612825220466	1,000 ft	Р
8920 0081000	Gray	612825220619	1,000 ft	Р
8920 0051000	Green, Dark	612825348047	1,000 ft	Р
8920 0031000	Orange	612825220534	1,000 ft	Р
8920 002100	Red	612825220497	100 ft	
8920 0021000	Red	612825220503	1,000 ft	Р
8920 0025000	Red	612825220510	5,000 ft	
8920 0071000	Violet	612825220596	1,000 ft	Р
8920 009100	White	612825220640	100 ft	
8920 0091000	White	612825220657	1,000 ft	Р
8920 004100	Yellow	612825220558	100 ft	
8920 0041000	Yellow	612825220565	1,000 ft	Р

Footnote:	C - CRATE REEL PUT-UP.
Footnote:	P - STRIPE COLORS ON STOCK SOLID COLORS. STRIPING ADDER OF \$8.00/M= FOR 1 OR 2 STRIPES. 10,000' MINIMUM ORDER FOR COLOR COMBINATION. PUT-UP WILL BE SUBJECT TO TWO PIECES (+ OR -) 10% PER SPOOL, WITH A MINIMUM LENGTH OF 100'.

History

Update and Revision:	Revision Number: 0.259 Revision Date: 04-08-2020

© 2020 Belden, Inc

All Rights Reserved

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.