


P	LTR	DESCRIPTION	DATE	DWN	APVD
B		ECR-14-013486	17SEP14	SW	RZ
B2		REVISE NOTES	27OCT2015	BB	JC
B3		OBSOLETE PER ECR-16-006201	08JUL2016	DEH	JC



PART NUMBER	A/m	△
2123287-1	2	±0.15
2123287-2	3	±0.15
2123287-3	5	±0.15
2123287-4	10	±0.15
2123287-5	15	±0.15
2123287-6	20	±0.20
2123287-7	25	±0.25
2123287-8	30	±0.30
2123287-9	40	±0.40
1-2123287-0	50	±0.50
1-2123287-1	100	±1.00
1-2123287-2	1	±0.15
1-2123287-3	7	±0.15

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN L. CASTAGNA 27APR2010	TE Connectivity	
DIMENSIONS: mm		CHK R. FAIR 27APR2010	NAME PARALIGHT CABLE ASS'Y, 4X10 QSFP	
TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ± 1 PLC ±0.5 2 PLC ±0.13 3 PLC ±0.013 4 PLC ±0.0001 ANGLES ± FINISH		APVD R.D. MILLER 27APR2010	SIZE A200779	
MATERIAL		PRODUCT SPEC APPLICATION SPEC WEIGHT	DRAWING NO C-2123287	
		CUSTOMER DRAWING	RESTRICTED TO	
		SCALE 1:1	SHEET 2 OF 2	
			REV B3	

QSFP	
PIN NO.	SIGNAL
1	GND 
2	Tx2n
3	Tx2p
4	GND 
5	Tx4n
6	Tx4p
7	GND 
8	ModSelL
9	ResetL
10	Vcc Rx 
11	SCL
12	SDA
13	GND 
14	Rx3p
15	Rx3n
16	GND 
17	Rx1p
18	Rx1n
19	GND 
20	GND 
21	Rx2n
22	Rx2p
23	GND 
24	Rx4n
25	Rx4p
26	GND 
27	ModPrsL
28	ModPrsH
29	Vcc Tx 
30	Vcc I
31	PRMode
32	GND
33	Tx1p
34	Tx1n
35	GND
36	Tx1p
37	Tx1n
38	GND 

BAR CODE-- S/N: DBMM DDNNNNN

TE-AC01- = PREFIX (LAW ENFORCEMENT SAFETY ID) TE P/N- TE P/N-
X-2123287-X = TE IDENTIFICATION NUMBER TE-AC01-2123287-X
X-2123287-X = TE IDENTIFICATION NUMBER MANUFACTURED IN US OF



Length: XXXm
REV.B2

S = SERIAL NUMBER BBBMMYYDDDDNNNNN
 B = BUILDING NUMBER
 M = MANUFACTURING LOCATION
 YY = TWO DIGIT YEAR
 DDD = ORDINAL DATE
 NNNNN = FIVE DIGIT SERIAL NUMBER

COUNTRY OF ORIGIN
WHEN MANUFACTURED
OUTSIDE THE US LABEL
MUST READ 'MADE IN XXXXX'.
-- WHERE XXXXX REPRESENTS
THE COUNTRY OF MANUFACTURING

```
-- LENGTH FROM PART NUMBER TABLE
-- TE LOGO & CUSTOMER PRINT REV
```

5 TRACE LABEL INFORMATION

NOTE: LASER SAFETY CERTIFICATION IS BASED ON THE PREFIX
AND THAT TE IS THE ONLY MANUFACTURE VISIBLE ON
THE LABEL.

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN 27APR2010 L. CASTAGNA CHK 27APR2010 R. FAIR APVD 27APR2010 R. D. MILLER		 TE Connectivity	
DIMENSIONS: mm 		TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ±.5 1 PLC ±0.13 2 PLC ±0.13 4 PLC ±0.0001 ANGLES ±.		NAME PARALIGHT CABLE ASS'Y, 4X10 QSFP -	
MATERIAL -		PRODUCT SPEC - APPLICATION SPEC - WEIGHT -		SIZE A2	CAGE CODE 00779
		CUSTOMER DRAWING		DRAWING NO C-2123287	RESTRICTED TO -
				SCALE 1:1	SHEET 2 OF 2
				REV B3	

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[1-2123287-1](#)