



FEATURES:

- This in-line banana plug is ideal for making patch cords and field repairs.
- A snap-on two piece design allows the wire to be crimped or soldered to the banana plug.
- Parts will accept 18, 20, 22 AWG. Wire, crimp or solder connection.
- Use with Model #5167 to build a custom extension cable.

MATERIALS:

In-Line Banana Plug

Plug body: Brass per QQ-B-626, Alloy 360, ½ Hard

Spring: Beryllium copper per ASTM B194, Alloy 172, Cond. HT.

Insulation: Flexible PVC. Color: See Ordering Information

Marking: "POMONA"

Finish: Banana Plug – Nickel plated per QQ-N-290, Class 2, 200/300 micro-inches.

Rating: (Independent of Wire)

Operating Temp. +50°C. (+122°F.) Max.

Voltage: 5000 VDC

Current: 15 Amperes

RATINGS: (Independent of Wire)

Operating Temperature: +50°C. (+122°F.) Max.

Voltage: Hand-held testing 30VAC/60VDC Max.

Hands free testing in controlled voltage environments: 5000 WVDC Max.

Current: 15 Amperes

ORDERING INFORMATION: Model 5169-*

*= Color, -0 Black, -2 Red

Ordering example: 5169-0, Color is Black

Other colors available on special request.

All dimensions are in inches. Tolerances (except noted): .xx = $\pm .02"$ (.51 mm), .xxx = $\pm .005"$ (.127 mm).

All specifications are to the latest revisions. Specifications are subject to change without notice.

Registered trademarks are the property of their respective companies. Made in USA

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Pomona:

5169-4 5169-02