



M12 A-coded 4-pole, female straight connector
for technical details see DS 21035001004



Loading-Plan:

1	brown
2	white
3	blue
4	black

- Protection level: IP67
- Temperature range: -25°C ... +80°C




length in "1m" step	40	XXX=400
	39	XXX=390
	.	.
	12	XXX=120
length in "0.1m" step	11	XXX=110
	10	XXX=100
	9.9	XXX=099
	9.8	XXX=098
	.	.
	0.4	XXX=004
	0.3	XXX=003
	0.2	XXX=002
	0.1	XXX=001
Step	a [m]	XXX

4.0 to 40	+1%
0.1 to 3.9	+0.04
a [m]	Tolerance

Part no.	213485004XXXXX
----------	----------------

Type of cable	XX
PVC grey, 4x0.34mm ²	XX=84
PUR black, 4x0.34mm ²	XX=91

	All rights reserved		Scale 2:1	Free size tol.		Ref.	
	Department EC PD - RO		Created by POPESCU	Inspected by AVRAM	Standardisation HOFFMANN	Date 2015-12-17	State Final Release
HARTING Electronics GmbH		Title M12 A-coded Cable Assembly				Doc-Key / ECM-Nr. 100578831/UGD/009/B 500000098541	
D-32339 Espelkamp		Type TB	Number 213485004XXXXX			Rev. B	Page 1/1

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

HARTING:

[21348500484100](#)