
## Overall Width (OW) Opening **STATSHIELD® Static Shielding Bag Metal In Construction** Discharge Shielding RoHS Length (L) ATTENTION: ATTENTION: Contents may be Static Sensitive OTHER PET/ALU/PE Handling Precautions Required DescoIndustries.com Made in America Date & Lot Code Printed for QC Traceablility Weld Weld Width (W Seal



Side Weld Seals 3/8 in. (±0.10)

#### **Mixed Unsortable Plastic Scrap**

Mixed unsortable plastic scrap shall contain assorted plastics of multiple grades that are co-extruded, bonded or laminated together which are unsortable into individual grades

Desco's bags are recyclable

Soft Fold Bottom

Statshield® bags are packaged 100 per package in an oversized shielding bag. See Shielding Bag Storage at TB-7057.

#### STATSHIELD® METAL-IN SERIES

### **Specifications:**

Surface Resistance:

**Standard Document** 

ANSI/ESD S541 (ANSI/ESD S20.20)

ANSI/ESD S11.4

#### **Electrical Properties Typical Values**

 $1 \times 10^4 \text{ to} < 1 \times 10^{11} \text{ ohms}$ Outer Surface  $1 \times 10^4 \text{ to} < 1 \times 10^{11} \text{ ohms}$ Inner Surface Discharge Shielding <20 nJ

Charge Generation Teflon: 0.09 nC/sq. in.

Capacitance Probe (to dissipate 1 KV) <30 volts Meets Requirements of:

**ESD Protective Packaging** Level 3 Technical Requirements

Test Procedures/Method

ANSI/ESD STM11.11 ANSI/ESD STM11.11

ANSI/ESD STM11.31, EIA 541 Modified Incline Plane Modified Incline Plane

ANSI/EIA-541/Appendix E, 1kV Discharge

**Physical Properties** 

Film Thickness Nominal 0.0030" (0.0762mm) ±10% MIL-STD-3010, 1003

Width (Inside Dimensions) Nominal -0" / + 0.125"

Length (Inside Dimensions) Nominal ± 0.125" Light Transmission >40% (Tobias) Heat Seal >10 lbs/in

Tensile Strength 4600 PSI, 32 MPa Puncture Resistance >10 lbs

Non-corrosive Pass Silicone Not detected

Marking Adhesion Pass

**ASTM D-1003** 

375°F, 1/2 sec 60 psi ASTM D882

MIL-STD-3010, 2065

MIL-STD-3010, M3005

**FTIR** 

IPC-TM-650 2.4.1

#### ANSI/ESD S541 Section 6.2 Outside an EPA

"Transportation of sensitive products outside of an EPA shall require packaging that provides:

Quartz: 0.01 nC/sq. in.

- 1. Low charge generation
- 2. Dissipative or conductive materials for intimate contact
- 3. A structure that provides electrostatic discharge shielding."

#### RoHS, REACH, and Conflict Minerals Statement:

See RoHS. REACH, and Conflict Minerals Statement at Desco.com.

#### **Limited Warranty**

See Desco's Limited Warranty at Desco.com

Statshield® and Statfree® are Registered Trademarks of Desco Industries Inc. See Bag Selection Chart Click HERE.



Made in the United States of America

Specifications and procedures subject to change without notice.

# STATSHIELD® BAG, SHIELDING, METAL-IN, 0.0030" (0.0762mm)



DESCO WEST: 3651 WALNUT AVE., CHINO, CA 91710 WEB SITE: Desco.com

PHONE (909) 627-8178

DESCO EAST: ONE COLGATE WAY, CANTON, MA 02021-1407

PHONE (781) 821-8370

**DRAWING** NUMBER 13405

DATE: January 2018

# **Mouser Electronics**

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

# Desco:

13430	13445	13465	13470	13415	13460	13405	13505	13524	13500	13457	13410	13435	13531	13469
13511	13495	13509	13401	13467	13529	13446	13449	13494	13518	13490	13420	13450	13521	13516
13528	13444	13416	13471	13459	13402	13453	13425	13476	13527	13448	13403	13440	13533	13515
13428	13424	13526	13443	13517	13498	13480	13508	13458	13429	13530	13497	13506	13442	13456
13468	13454	13466	13464	13447	13475	13520	13485	13510						