




ST2 Series




Panel Cutout




Bushing Options



Terminal Options



Water Protection Options



FEATURES:

- Heavy Duty Rating with UL Approvals
- Many Functions Available
- Tab, Screw, and Solder Terminal Options
- Rubber Boot for Water and Dust Protection

SPECIFICATIONS:

RATING: MAINTAINED SWITCHES:

20A 125VAC [cULus]
15A 250VAC [cULus]
2HP 125-250VAC [cULus]

MOMENTARY SWITCHES:

20A 125VAC [cULus]
15A 250VAC [cULus]
1.5HP 125-250VAC [cULus]

TEMPERATURE: -20°C to 85°C

ELECTRICAL LIFE: 6,000 Cycles

CONTACT RESISTANCE: 50mΩ Max.

INSULATION RESISTANCE: 800MΩ Min. at 500VDC

DIELECTRIC STRENGTH: 1,500VAC for 1 Minute

MATERIALS:

Body: Phenolic, UL94 V-0

ACTUATOR: Nickel Plated Brass

BUSHING: Nickel Plated Brass

HOUSING: Stainless Steel

CONTACTS: Silver Alloy

TERMINALS: Silver Plated Brass

Series	Terminal	Function	Rating	Actuator Type	Bushing Type
ST2	1 - 4.8mm Tabs 2 - Solder 4 - 6.3mm Tabs 6 - Screw	2 Pole: 2 - Off-On G - On-On E - Off(On) 6 - On-Off-On J - On-Off(On) K - (On)-(Off)(On)	D - 20A 125VAC	0 - Standard Bat	0 - M12x1.0 2 - 15/32"-32UNS
Variable Length: Wx - Wire Leads (x in Inches)					

Note:
Terminal bridging options available. See "Z02" function for polarity reversal in example photo.



ST226D00
ACC-B03-2
ACC-M01-3

ST24Z02D00



Accessories Series	Type	Options
ACC	Rubber Boot: B03 - For Standard Bat	Colors for Boot: 2 - Black
	Hardware: N02 - Knurled Nut	Threading: 3 - 15/32"-32UNS 5 - M12x1.0

EXAMPLE PART NUMBERS:

ST242D00 2P Off-On
Standard Actuator/Bushing, 0.250" QC

ST246D00 2P On-Off-On
Standard Actuator/Bushing, 0.250" QC



E-SWITCH®

www.e-switch.com

800.867.2717

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

E-Switch:

[ST24ED00](#) [ST246D00](#) [ST24KD00](#) [ST24GD00](#) [ST242D00](#) [ST24Z02D00](#) [ST26GD00](#) [ST22ED00](#) [ST26ED00](#)
[ST24Z04D00](#) [ST22GD00](#) [ST26KD00](#) [ST24JD00](#) [ST262D00](#) [ST226D00](#) [ST22KD00](#) [ST266D00](#) [ST222D00](#)