




1

CONTACT CAVITIES IDENTIFIED BY CHARACTERS ON FRONT AND REAR FACES OF CONNECTOR.

2

#4 FASTENER RECOMMENDED FOR -1 MOUNTING.
#4 FASTENER REQUIRED FOR -2 MOUNTING.

CONTACT BODY: .000030 MIN GOLD FOR A LENGTH OF .250 MIN FROM MATING END, WITH REMAINDER TO BE GOLD FLASH, BOTH OVER .000050 MIN NICKEL.
CONTACT POST: .000100 MIN TIN-LEAD OVER .000100 MIN COPPER.

PC BOARD HOLE PATTERN IS DEFINED RELATIVE TO CONNECTOR C.L. AND PANEL MOUNTING FACE INDICATED.

CONTACT BODY: .000030 MIN GOLD FOR A LENGTH OF .250 MIN FROM MATING END, WITH REMAINDER TO BE GOLD FLASH, BOTH OVER .000050 MIN NICKEL.
CONTACT POST: .000100 MIN TIN OVER .000100 MIN COPPER.

RECOMMENDED
PANEL CUTOUT

	W/INSERTS	1-796403-2
	W/O INSERTS	1-796403-1
	W/INSERTS	-796403-2-
	W/O INSERTS	796403-1

OBSOLETE

CONTACT FINISH	CONFIG.	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:
INCHES

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC	±	-
1 PLC	±	-
2 PLC	±	.03
3 PLC	±	.010
4 PLC	±	-
ANGLES	±	-

MATERIAL

-

FINISH

-

DWN
HAMNER
2-19-00

CHK
M.CHACKO
2-24-00

APVD
M.CHACKO
2-24-00

PRODUCT SPEC

APPLICATION SPEC

WEIGHT

CUSTOMER DRAWING

TE Connectivity

NAME
RECEPTACLE ASSY, POSTED, RT ANGLE,
STD SEX, SIZE 11-4, SERIES 1, CPC

SIZE
A2

CAGE CODE
00779

DRAWING NO
796403

RESTRICTED TO
-

SCALE
2:1

SHEET
1 of 1

REV
E1

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[796403-1](#)