

SMA and Reverse Polarity SMA Specifications

Materials		
Connector Part	Material	Finish
Bodies	Brass	Nickel or Gold
	Stainless Steel	Passivated or Gold
Center contact	Male: Brass	Gold
	Female: Beryllium Copper	
Insulator	PTFE	N/A
Crimp ferrule	Annealed Copper	Nickel or Gold

Electrical			
Electrical Data	Detail		
Impedance	50 ohm		
Frequency range	Flexible cable: 0~12.4GHz		
	Semi-rigid cable: 0~18GHz		
Working voltage	RG402 (.141") » 500 volts rms max.		
	RG405 (.085") » 335 volts rms max.		
	RG58, 141, 142, 223/U » 500 volts rms max.		
	RG174, 188, 316/U » 335 volts rms max.		
	RG178, 196/U » 250 volts rms max.		
Insulation resistance	5,000 megaohms min.		
Dielectric withstanding voltage	RG402 (.141") » 1,000 volts rms max.		
	RG405 (.085") » 750 volts rms max.		
	RG58, 141, 142, 223/U » 1,000 volts rms max.		
	RG174, 188, 316/U » 750 volts rms max.		
	RG178, 196/U » 500 volts rms max.		
Contact resistance	Center contact: 3.0 milliohms max.		
	Outer contact: 2.0 milliohms max.		
VSWR: f(GHz)		Straight	Right angle
	RG178/U	1.20+0.025f	1.20+0.03f
	RG174, 316/U	1.15+0.02f	1.15+0.03f
	RG58, 141, 142, 223/U	1.10+0.01f	1.15+0.02f
	RG402 (.141")	1.05+0.005f	1.15+0.15f
	RG405 (.085")	1.05+0.005f	1.18+0.15f
Insertion loss	0.04dB max. x \sqrt{f} GHz (straight)		
	0.06dB max. x \sqrt{f} GHz (right angle)		

Mechanical

Mechanical Data	Detail
Engagement force	60lbs min.
Disengagement force	15 inch-pound
Connector durability	500 cycles min.
Cable retention force	RG58, 141, 142, 223/U » 40lbs min.
	RG174, 188, 316/U » 20lbs min.

Environmental

Environmental Data	Detail
Corrosion (salt spray)	MIL-STD-202 METHOD 101 TEST CONDITION B
Thermal shock	MIL-STD-202 METHOD 107 TEST CONDITION B
Vibration	MIL-STD-202 METHOD 204 TEST CONDITION D
Mechanical shock	MIL-STD-202 METHOD 213 TEST CONDITION I
Temperature Range	-65°C to 165°C

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Linx Technologies:](#)

[CONREVSMA015-R58](#) [CONREVSMA004](#) [CONREVSMA005-R178](#) [CONREVSMA014-R178](#) [CONREVSMA014-R58](#)
[CONREVSMA011-R58](#) [CONREVSMA003.031-L](#) [CONREVSMA008](#) [CONREVSMA007](#) [CONREVSMA013.062](#) [ADP-](#)
[RPSM-SMAF](#) [CON SMA015](#) [CON SMA005](#) [CON SMA005-R178](#) [CON SMA008](#) [CON SMA007](#) [CON SMA007-R178](#)
[CON SMA007-R58](#) [CON SMA012](#) [ADP-SMAM-SMAM](#)