

# Housing - HC-B 16-KML-80/M1PG21 - 1687710

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



HEAVYCON coupling housing B16, with single locking latch, height 80 mm, with screw connection 1x Pg21



## **Key Commercial Data**

Packing unit	10 pc
GTIN	4 017918 837792
GTIN	4017918837792

### Technical data

#### **Dimensions**

Height	80 mm
Width	43 mm
Length	94 mm
Wrench size, union nut	28 mm
External cable diameter	10 mm 19 mm

#### Ambient conditions

Degree of protection of housing (IP)	IP65
Ambient temperature (operation)	-40 °C 125 °C

#### General

Note	For contact inserts HC-B16, BB32, BBB40, D40, DD72, HS6, M, K		
Size	B16		
Housing type	Coupling housings		
Locking type	with single locking latch		
No. of cable outlets	1		
Cable outlet	straight		
Screw connection	with		
Type of the screw connection	1x Pg21		

12/07/2018 Page 1 / 3



# Housing - HC-B 16-KML-80/M1PG21 - 1687710


## Technical data

### General

Housing material	Aluminum die-cast
Housing surface material	Powder-coated, gray
Seal material	NBR
Cable gland material	Nickel-plated brass
Cable seal material	NBR
Material lock	Stainless steel, handle: PA
Material grip body interlock	PA

## Drawings

### Dimensional drawing



Approvals			
Approvals			
Approvals			
EAC			
Ex Approvals			

Approval details

EHC EAC EAC-Zulassung



Phoenix Contact 2018 © - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany Tel. +49 5235 300 Fax +49 5235 3 41200

http://www.phoenixcontact.com

# **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Phoenix Contact: