

Customer Information Sheet

DRAWING No.: M80-405XXXX

SHEET 2 OF 2

IF IN DOUBT - ASK

(C)

NOT TO SCALE

THIRD ANGLE PROJECTION

ALL DIMENSIONS IN mm

SPECIFICATIONS:

MATERIAL:
MOULDING = GLASS-FILLED PPS, UL94V-0, BLACK
CONTACT CLIP = BERYLLIUM COPPER
CONTACT SHELL = BRASS
JACKSCREW = STAINLESS STEEL

FINISH:
01 = 0.3 μ GOLD CLIP, 3.5-5.0 μ TIN/LEAD SHELL
05 = 0.3 μ GOLD CLIP, 0.25-0.3 μ GOLD SHELL
42 = 0.3 μ GOLD CLIP,
3.5-5.0 μ 100% TIN OVER NICKEL SHELL

ELECTRICAL:
CURRENT RATING AT 25°C = 3.0A MAX
CURRENT RATING AT 85°C = 2.2A MAX
WORKING VOLTAGE = 800V AC/DC
VOLTAGE PROOF = 1200V AC/DC
CONTACT RESISTANCE = 25 m Ω MAX
INSULATION RESISTANCE = 100 M Ω MIN

MECHANICAL:
DURABILITY = 500 OPERATIONS
INSERTION FORCE (ϕ 0.5mm GAUGE) = 2.8N MAX

WITHDRAWAL FORCE (ϕ 0.5mm GAUGE) = 0.2N MIN





ENVIRONMENTAL:

TEMPERATURE RANGE = -55°C TO +125°C


PACKING:

TUBE

FOR COMPLETE SPECIFICATION, SEE COMPONENT
SPECIFICATION C005XX (LATEST ISSUE)



DIMENSION	CALCULATION
DIM 'A'	TOTAL No. OF CONTACTS - 2
DIM 'B'	TOTAL No. OF CONTACTS + 5
DIM 'C'	TOTAL No. OF CONTACTS + 10
EXAMPLE: CONNECTOR WITH 20 CONTACTS, GOLD CLIP AND 100% TIN SHELL, M80-4052042	
DIM 'A' = 18.00mm, DIM 'B' = 25.00mm, DIM 'C' = 30.00mm	



ORDER CODE:
M80-405XXXX

TOTAL No. OF CONTACTS
04 TO 50
(EVEN NUMBERS ONLY)

FINISH CODE
01 - GOLD CLIP, TIN/LEAD SHELL
05 - GOLD CLIP, GOLD SHELL
42 - GOLD CLIP, 100% TIN OVER NICKEL SHELL

SB	2	15.07.13	12139
NAME	ISS.	DATE	C/NOTE
APPROVED:	S. BENNETT		
CHECKED:	S. FLOWER		
DRAWN:	B. M. KENT		
CUSTOMER REF.:			
ASSEMBLY DRG.:			

ASSEMBLY DRG.:

ASSEMBLY DRG.:

TITLE: JACKSCREW DATAMATE
DIL VERTICAL PC-TAIL FEMALE
'REVERSE FIX' AND BOARD-MOUNT
DRAWING NUMBER:
M80-405XXXX

SHT
2
OF
2

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Harwin:

[M80-4050601](#) [M80-4051001](#) [M80-4051042](#) [M80-4051201](#) [M80-4051242](#) [M80-4051401](#) [M80-4051442](#) [M80-4051801](#) [M80-4051842](#) [M80-4052042](#) [M80-4052601](#) [M80-4052642](#) [M80-4053401](#) [M80-4053442](#) [M80-4054201](#) [M80-4055001](#) [M80-4050605](#) [M80-4054205](#) [M80-4055005](#) [M80-4051405](#) [M80-4051005](#) [M80-4051205](#) [M80-4050805](#) [M80-4051605](#) [M80-4053405](#) [M80-4052605](#) [M80-4052005](#) [M80-4050405](#) [M80-4050801](#)