UNCONTROLLED DOCUMENT		RT NUMBER	REV.
	SSA-	-LXB10IW	D
	REV. E.C.N. NUMBER A	ND REVISION COMMENT	S DATE
1.74 [0.069] 2.54 [0.100]	A CHG'D SAVE OPER		6.7.94
(10 PLS.) - (9 PLS.) - (8.00 [0.315] - (9 PLS.)	B CHG'D SAVE OPER		8.29.94
PIN 20 -		& #10BRDR. & REDRAN	VN. 5.12.99
	D E.C.N. #10BRDR.	& REDRAWN.	7.2.01
	·		·
5.08 [0.200]			
	ELECTRO-OPTICAL CHARACTERISTIC	CS TA=25'C If=20mA	
	PARAMETER MIN	TYP MAX UNITS	TEST COND
ANDDE / PIN 1 PIN 10 -	PEAK WAVELENGTH	635 nm	
MARK 0.20 F0.0153	FORWARD VOLTAGE	2.0 2.5 V <sub>f</sub>	
MARK - 0.38 [0.015] (2 PLS.)	REVERSE VOLTAGE 5.0	Vr	lr=100µA
	AXIAL INTENSITY VIEWING ANGLE	8 mcd 160 2x theta	lf=20mA
	EMITTED COLOR: RED		
	EPOXY LENS FINISH: MILKY WHI	TE DIFFUSED	
	FACE COLOR: BLACK		
	IMITS OF SAFE OPERATION AT 2	5°C PER CHIP	
	PARAMETER	MAX	UNITS
2.54 [0.100] (9 PLS.) (10 PLS.) ©	PEAK FORWARD CURRENT* STEADY CURRENT	150 30	mA mA
	STEADT CORRENT		mW
	POWER DISSIPATION	105	11199
	POWER DISSIPATION DERATE FROM 25°C	105 	
			mW/'C C
22.86 [0.900] —	DERATE FROM 25°C OPERATING, STORAGE TEMP. SOLDERING TEMP.	- 1.2	m₩/'℃ ℃
	DERATE FROM 25°C OPERATING, STORAGE TEMP. SOLDERING TEMP. 2.0mm FROM BODY	-1.2 -40 T0 +85	mW/°C °C
22.86 [0.900]	DERATE FROM 25°C OPERATING, STORAGE TEMP. SOLDERING TEMP.	-1.2 -40 T0 +85	m₩/'℃ ℃
22.86 [0.900] <u>TOP VIEW POLARITY</u> 20 19 18 17 16 15 14 13 12 11 1 1 1 1 1 1 1	DERATE FROM 25°C OPERATING, STORAGE TEMP. SOLDERING TEMP. 2.0mm FROM BODY	-1.2 -40 T0 +85	m₩/'℃ ℃
$\begin{array}{c} \hline & \hline & \hline \\ \hline & \hline & \hline \\ \hline & \hline & \hline \\ \hline & \hline &$	DERATE FROM 25°C OPERATING, STORAGE TEMP. SOLDERING TEMP. 2.0mm FROM BODY	-1.2 -40 T0 +85	m₩/'℃ ℃
22.86 [0.900] <u>TOP VIEW POLARITY</u> 20 19 18 17 16 15 14 13 12 11 1 1 1 1 1 1 1	DERATE FROM 25°C OPERATING, STORAGE TEMP. SOLDERING TEMP. 2.0mm FROM BODY	-1.2 -40 T0 +85	m₩/'℃ ℃
$\begin{array}{c} \hline & \hline & \hline \\ \hline & \hline & \hline & \hline & \hline & \hline & \hline &$	DERATE FROM 25°C OPERATING, STORAGE TEMP. SOLDERING TEMP. 2.0mm FROM BODY * t<10µS	- 1.2 - 40 T0 + 85 + 260	mW/*C *C *C 3 SEC. MAX
$\begin{array}{c} \hline \hline$	DERATE FROM 25°C OPERATING, STORAGE TEMP. SOLDERING TEMP. <u>2.0mm FROM BODY</u> * t<10µS	-1.2 -40 T0 +85 +260	mW/C *C 3 SEC. MAX
$\begin{array}{c} \hline & \hline $	DERATE FROM 25°C OPERATING, STORAGE TEMP. SOLDERING TEMP. <u>2.0mm FROM BODY</u> * t<10µS	- 1.2 - 40 T0 + 85 + 260 ROLLED DOG 75 (±0.030). MIN= +DECIMAL PRECISION	mW/C 'C <u>3 SEC. MAX</u>
$\frac{\text{TOP VIEW POLARITY}}{20 \ 19 \ 18 \ 17 \ 16 \ 15 \ 14 \ 13 \ 12 \ 11}$ $\frac{1}{2 \ 7 \ 7 \ 7 \ 7 \ 7 \ 7 \ 7 \ 7 \ 7 \ $	DERATE FROM 25°C OPERATING, STORAGE TEMP. SOLDERING TEMP. <u>2.0mm FROM BODY</u> * t<10µS LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.7	- 1.2 - 40 T0 + 85 + 260	mW/C C C 3 SEC. MAX CUMENT MAX.= +0.00 MAX.= +0.00 MAX.= -DECIMAL PRECISION
$\frac{100 \text{ VIEW POLARITY}}{1 2 0 19 18 17 16 15 14 13 12 11}$ $\frac{1}{4} \xrightarrow{1}{4} \xrightarrow{1}{4}$	DERATE FROM 25°C OPERATING, STORAGE TEMP. SOLDERING TEMP. 2.0mm FROM BODY * t<10µS * t<10µS	- 1.2 - 40 T0 + 85 + 260 POLLED DOC (±0.030). MIN= +DECIMAL PRECISION 290 E. HELEN ROAD PALATINE, IL 60067 PHONE: + 1.847.359.	mW/C 'C <u>3 SEC. MAX</u> <u>- 000</u> MAX.= +0.00 MAX.= +0.00 MAX.= -DECIMAL PRECISION DIC 2790
$\frac{100 \text{ VIEW POLARITY}}{1 2 0 19 18 17 16 15 14 13 12 11}$ $\frac{1}{1 2 3 4 5 6 7 8 9 10}$ $\frac{100 \text{ VIEW POLARITY}}{1 2 3 4 5 6 7 8 9 10}$ $\frac{100 \text{ VIEW POLARITY}}{1 2 3 4 5 6 7 8 9 10}$ $\frac{100 \text{ VIEW POLARITY}}{1 2 3 4 5 6 7 8 9 10}$ $\frac{100 \text{ VIEW POLARITY}}{1 2 3 4 5 6 7 8 9 10}$ $\frac{100 \text{ VIEW POLARITY}}{1 2 3 4 5 6 7 8 9 10}$ $\frac{100 \text{ VIEW POLARITY}}{1 2 3 4 5 6 7 8 9 10}$ $\frac{100 \text{ VIEW POLARITY}}{1 2 3 4 5 6 7 8 9 10}$ $\frac{100 \text{ VIEW POLARITY}}{1 2 3 4 5 6 7 8 9 10}$	DERATE FROM 25°C OPERATING, STORAGE TEMP. SOLDERING TEMP. 2.0mm FROM BODY * t<10µS UNCONT LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.7 MEX NO CONTRACTOR SIZE=±0.05 (±0.002), LEAD LENGTH=±0.7	-1.2 -40 T0 + 85 +260 75 (±0.030). MIN= +DECIMAL PRECISION 290 E. HELEN ROAD PALATINE, IL 60067 PHONE: +1.847.359. US WEB: www.jumex.	mW/C 'C 3 SEC. MAX <u>CUMENT</u> MAX.= +0.00 MAX.= +0.00 MAX.= -DECIMAL PRECISION C-6976 2790 corr
IOP VIEW POLARITY         20       19       18       17       16       15       14       13       12       11         Image: Im	DERATE FROM 25°C OPERATING, STORAGE TEMP. SOLDERING TEMP. 2.0mm FROM BODY * t<10µS () LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.7 () LEAD SIZE=±0.7 () L	- 1.2 - 40 T0 + 85 + 260 POLLED DOC (±0.030). MIN= +DECIMAL PRECISION 290 E. HELEN ROAD PALATINE, IL 60067 PHONE: + 1.847.359.	mW/C 'C 3 SEC. MAX <u>CUMENT</u> WX.= +0.00 MAX -000 MAX PRECISION DIC 2790 com com.tw
IOP VIEW POLARITY         20       19       18       17       16       15       14       13       12       11         Image: Im	DERATE FROM 25°C OPERATING, STORAGE TEMP. SOLDERING TEMP. 2.0mm FROM BODY * t<10µS LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.7 LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.7 DF ES. AT DRAWN BY: CHECKED	-1.2 -40 T0 +85 +260 75 (±0.030). MIN= +DECIMAL PRECISION 290 E. HELEN ROAD PALATINE, IL 60067 PHONE: +1.847.359. US WEB: www.lumex. TW WEB: www.lumex. TW WEB: www.lumex.	mW/C 'C 3 SEC. MAX <u>CUMENT</u> WX.= +0.00 MAX -000 MAX PRECISION DIC 2790 com com.tw

## **Mouser Electronics**

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Lumex: SSA-LXB10IW