




LOC	DIST	REVISIONS						
		F	LTR	DESCRIPTION	DATE	OWN	APVD	
J	-		A	RELEASED	22MAR06	SS	SI	
		A1	REVISED	ECR-06-021383	04SEP06	SS	KS	
		B	REVISED	ECR-10-007503	23APR10	TS	KB	
		B1	REVISED	ECR-10-014182	05JUL10	TS	KB	

-1,-3:AS SHOWN
-1,-3:本図



A - A



1612275-3






TABLE-1

PAPER BOX ダンボール箱 SOFT TRAY プリスタートレイ	PAPER BOX ダンボール箱 SOFT TRAY プリスタートレイ	PAPER BOX ダンボール箱 SOFT TRAY プリスタートレイ	PAPER BOX ダンボール箱 SOFT TRAY プリスタートレイ	OUTER 外装 INNER 内装	PACKING STYLE 梱包形態		
I	I	I	I	BLACK	PBT	SLIDER-L	6
I	I	I	I	BLACK	PBT	SLIDER-R	5
I	I	I	I	REDDISH BROWN	SILICONE	SEAL RING	4
I	—//—	I	—//—	LIGHT GRAY	PBT	RETAINER 89POS	3
—//—	I	—//—	I	NATURAL		RETAINER 126POS	
I	I	I	I	BLACK	PBT	FRONT CAV	2
I	—//—	—//—	—//—	BLACK	PBT	PLUG HSG 89POS FOR CLIP	1
—//—	I	—//—	—//—			PLUG HSG 126POS FOR CLIP	
—//—	—//—	I	—//—			PLUG HSG 89POS	
—//—	—//—	—//—	I			PLUG HSG 126POS	
1612275-4	1612275-3	1612275-2	1612275-1	COLOR	MATERIAL	NAME	ITEM NO.
89POS	126POS	89POS	126POS	AVAILABLE CAVITY POS 使用可能キャビティ数			
69 g	69 g	70 g	70 g	NET WEIGHT 質量			






- MATING CONNECTOR IS(P/N):
1612275-1/-3(126POS):1612272(186POS)
1612275-2/-4(89POS):1717313(149POS)
- HANDLING OF THIS PART SHOULD FOLLOW INSTRUCTION SHEET NO.411-78084.
- COMPONENTS OF THIS PART;SEE TABLE-1.
- THIS PRODUCT IS SHIPPED WITH RETAINER PRE-LOCKED POSITION.
- ASSEMBLED BY CUSTOMER.
LEVER P/N FOR SUPPLEMENT(P/N):1612281
- PLEASE USE A WIRE COVER, WHEN YOU CANNOT SECURE THE WORKING SPACE BETWEEN A LEVER AND AN ELECTRIC WIRE.
- 1, -2 ARE THE CLIP NON-CORRESPONDENCES.

- 嵌合相手品番(P/N):
1612275-1/-3(126POS):1612272(186POS)
1612275-2/-4(89POS):1717313(149POS)
- 本製品の取扱は取扱説明書NO.411-78084に従うこと
- 本製品の構成部品:TABLE-1参照
- リテーナはロック状態で出荷される。
- レバーは顧客にて組立てられる。
補給用/リターン品番(P/N):1612281
- レバーと電線の隙間(作業スペース)が確保出来ない時はカバーを使用下さい。
- 1,-2は、フリップ非対応です。

DIMENSIONS: 単位: mm		TOLERANCES UNLESS OTHERWISE SPECIFIED: 寸法公差 ±0.3 1-PLC ±0.1 2-PLC ±0.01 3-PLC ±0.001 4-PLC ±0.0001 ANGLES FINISH 仕上げ		OWN S.SHISHIKURA CHK K.SAKAMAKI APVD S.ISOHATA PRODUCT SPEC 108-5891 APPLICATION SPEC 114-5336 WEIGHT SEE TABLE CUSTOMER DRAWING	22MAR06 22MAR06 NAME SEALD EFI ECU 0.64/2.311 I/O CONNECTOR 126POS/89POS PLUG HOUSING ASSY SIZE CASE CODE DRAWING NO 00779 SCALE 2:1 SHEET 1 OF 2 REV B1
-----------------------	--	---	--	--	---

LOC	DIST	REVISIONS				
		REV	LYR	DESCRIPTION	DATE	OWN
J	-	-	-	SEE SHEET 1	-	-

-2, -4: AS SHOWN
-2, -4: 本図



THE INFORMATION CONTAINED HEREIN IS UNCLASSIFIED EXCEPT WHERE SHOWN OTHERWISE. IT IS SUBJECT TO CHANGE WITHOUT NOTICE AND WITHOUT LIABILITY. THE INFORMATION CONTAINED HEREIN IS UNCLASSIFIED EXCEPT WHERE SHOWN OTHERWISE. IT IS SUBJECT TO CHANGE WITHOUT NOTICE AND WITHOUT LIABILITY.		OWN		Tyco Electronics Corporation Kawasaki, Japan	
DIMENSIONS: 単位: mm		CHK		NAME 氏名	SEALED EFI ECU 0.64/2.311 I/O CONNECTOR 126POS/89POS PLUG HOUSING ASSY
TOLERANCES UNLESS OTHERWISE SPECIFIED: 一般公差 1 PLC ±0.1 2 P/B GLE ±0.01 3 PLC ±0.001 4 PLC ±0.0001		APVD			
		PRODUCT SPEC 製品規格		SIZE 寸法	CASE CODE 箱形コード
MATERIAL 材料		APPLICATION SPEC 配線図/規格			
FINISH 仕上		WEIGHT 重量		DRAWING NO. 図番	
CUSTOMER DRAWING		SCALE 縮尺			
		2:1		2 OF 2	
				B1	

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[1612275-1](#)