

4		3		2		1					
THIS DRAWING IS UNPUBLISHED.		RELEASED FOR PUBLICATION		20							
© COPYRIGHT 20		BY -		ALL RIGHTS RESERVED.							
NOTES: 1. MATERIALS AND FINISH HOUSING: PA 6-6, UL 94-V0, COLOR GRAY. CLAMP: BRASS, NICKEL PLATED. TERMINAL: BRASS, TIN PLATED. CLAMPING SCREW: M3, BRASS, NICKEL PLATED. 2. MECHANICAL WIRE STRIPPING LENGTH : 5.0-6.0 mm MIN. PC BOARD HOLES DIAMETER : 1.1 mm MAX. PC BOARD THICKNESS : 2.4 mm RECOMMENDED TIGHTENING TORQUE FOR SCREW: 0.5 Nm. 3. ELECTRICAL WIRE SIZE RANGE : 16-30 AWG. MAX. VOLTAGE : 300 V MAX CURRENT : 13.5 A CONTACT RESISTANCE : <15 m Ohm INSULATION RESISTANCE : >1000 M Ohm (500V DC) 4. OPERATING TEMPERATURE RANGE: -40°C TO +110°C 5. END-TO-END STACKABLE W/INTERLOCK WITHOUT LOSS OF CENTERLINE SPACING. 6. RECOGNIZED UNDER THE COMPONENT PROGRAM OF UNDERWRITERS LABORATORIES INC., FILE NO E60677. 7. PACKED IN TRAY. 8. NOT CUMULATIVE TOLERANCE. 9. PHIL-SLOT HEAD SCREW: M3, BRASS, NICKEL PLATED.						REVISIONS					
						P	LTR	DESCRIPTION	DATE	DWN	APVD
							-	SEE SHEET 1	-	-	-
THIS DRAWING IS A CONTROLLED DOCUMENT.						DWN 27FEB2004 S. WELDON CHK 27FEB2004 C. RICHARD APVD 27FEB2004 C. RICHARD		TE Connectivity			
DIMENSIONS:		TOLERANCES UNLESS OTHERWISE SPECIFIED:		PRODUCT SPEC		NAME		TB, PCB MOUNT, SIDE WIRE ENTRY, STACK W/INTERLOCK, 5.00mm PITCH			
mm		0 PLC ±- 1 PLC ±0.3 2 PLC ±0.25 3 PLC ±- 4 PLC ±- ANGLES ±2°		108-20166		SIZE		CAGE CODE			
MATERIAL		FINISH		114-20079		DRAWING NO		RESTRICTED TO			
1		1		-		A200779		C-1546216			
CUSTOMER DRAWING						SCALE 4:1		SHEET 2 OF 2			
						REV B1					

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[1546216-7](#)