

Termination board - IBS PCI RI/I-T - 2730129

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Termination board, with copper connection and external power supply

Product Description

The slave controller boards are intelligent PC boards that link the PC to any position in the INTERBUS system. This makes it possible to set up powerful visualization stations which allow access to data in the INTERBUS system and the controller close to the application. Several cards can be installed simultaneously in one PC so that it is possible to visualize or monitor several INTERBUS lines in one single PC. The number of data words that the slave controller boards occupy in the INTERBUS system can be set between one and eighteen. The interface cards provide a freely configurable fast I/O channel for time-critical data and also support the INTERBUS parameter channel (PCP). The parameter channel provides an optional access to larger data blocks.

Why buy this product

- External 24 V DC power supply
- Direct integration into OPC-based visualization systems via OPC server
- Installation of several cards in a PC with monitoring of multiple INTERBUS lines
- Parameterization and diagnostics with Diag+
- Compatible driver
- Access to INTERBUS system data and controller data via visualization stations
- INTERBUS parameter channel (PCP) supported



Key Commercial Data

Packing unit	1 pc
GTIN	 4 017918 974183
GTIN	4017918974183

Technical data

Note

Utilization restriction	EMC: class A product, see manufacturer's declaration in the download area
-------------------------	---

Dimensions

Width	134 mm
-------	--------

Termination board - IBS PCI RI/I-T - 2730129

Technical data

Dimensions

Height	107 mm
Depth	20 mm

Ambient conditions

Degree of protection	IP00
Ambient temperature (operation)	0 °C ... 55 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C
Permissible humidity (operation)	95 % (non-condensing)
Permissible humidity (storage/transport)	95 % (non-condensing)

Control system

Control system	IBM-compatible PCs with PCI slot
Configuration tool	Own configurator on CD
Operating system	Windows NT
	Windows 2000
	Windows XP

Software interfaces

Driver	Windows NT
	Windows 2000
	Windows XP
Application interface	DDI
	OPC-DA server

Software requirements

Configuration tool	Own configurator on CD
--------------------	------------------------

Power supply

Power supply connection	Via PCI bus or 2-pos. MINI-COMBICON
Typical current consumption	1 A
Supply voltage	3.3 V DC (internal)
	5 V DC (internal)
	24 V DC (external)
Supply voltage range	18 V DC ... 30 V DC
Power dissipation	max. 5 W

General

Weight	201.9 g
Format	Short plug-in card, 1-slot

Data interfaces

Interface	INTERBUS remote bus, incoming
Connection method	9-pos. D-SUB pin strip
Transmission speed	500 kbps / 2 Mbps (can be switched)
Interface	INTERBUS remote bus, outgoing

Termination board - IBS PCI RI/I-T - 2730129

Technical data

Data interfaces

Connection method	9-pos. D-SUB socket strip
Transmission speed	500 kbps / 2 Mbps (can be switched)
Interface	Host system
Connection method	PCI slot in acc. with PCI specification 2.1 or higher, PCI bus, 32 bits, 33 MHz, 3.3/5 V
Interface	External power supply
Connection method	2-pos. MINI PCB terminal block
Interrupts	1 IRQ, PNP

Direct I/Os

Number of pulse direction outputs	0
Limit frequency	0 kHz
Number of inputs	0
Input frequency	0 kHz

Fieldbus function

Amount of process data	max. 8192 Byte (INTERBUS-Master)
	256 Bit (INTERBUS-Slave)
Number of parameter data	4 Byte
Number of supported devices	max. 512 (of which 254 are remote bus devices/bus segments)
Number of devices with parameter channel	max. 126

Standards and Regulations

Connection in acc. with standard	CUL
----------------------------------	-----

Environmental Product Compliance

China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Phoenix Contact 2018 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Phoenix Contact:](#)

[2730129](#)