



この寸法は嵌合力によって管理する。

断面 A-A
尺度 8-1



断面 B-B



断面 C-C

注)

1. 嵌合するファストンタブの詳細については CP 063-045J の図面参照のこと。

2. OBSOLETE PART NUMBER

バラ状端子型番	連鎖状端子型番	材 料	仕 上	寸法 "H"	嵌合相手寸法
170048-1	170043-1	黄銅 0.25t	—	3.6	0.5±0.025
170048-2	170043-2	黄銅 0.25t	錫めき		
170048-4	170043-4	磷青銅 0.25t	錫めき		
170048-5	170043-5	錫めき黄銅 0.25t	—		
170048-6	170043-6	黄銅 0.25t	錫めき	3.3	
170048-7	170043-7	磷青銅 0.25t	錫めき		

単位: 寸 法 DIMENSIONS IN MM DO NOT SCALE PRINT

B2 REVISED PER ECR-15-016360		NK	LP	10MAR16	参考図面 (CUSTOMER COPY) (REFERENCE ONLY)	
LTR	発 行 REVISION RECORD)	DR	CHK	DATE	TE Connectivity	
DR 4-21 '75 H. Shibasaki		DE 5/12/75 J. Matsumoto		表参照		
CHK 5/23/75 M. Spindler		APP 5/19/75 Y. Sato		表参照		
4-21 '75		5/12/75		一般公差 TOLERANCE EXCEPT AS NOTED		
4-21 '75		5/12/75		±0.4 ±0.15 ±1.0		
4-21 '75		5/12/75		名称 (NAME)		
4-21 '75		5/12/75		"110" シリーズ ファストン リセプタクル (バラ状)		
4-21 '75		5/12/75		材料 (MATERIAL)		
4-21 '75		5/12/75		仕上 (FINISH)		
4-21 '75		5/12/75		平均電線断面積 (WIRE RANGE)		
4-21 '75		5/12/75		0.20~0.56 mm² (AWG 24-20)		
4-21 '75		5/12/75		被覆外径 (INSULATION DIA)		
4-21 '75		5/12/75		2.0~3.0 mm (080-120IN)		
4-21 '75		5/12/75		分類 CLASS		
4-21 '75		5/12/75		ファストン		
4-21 '75		5/12/75		型式 (TYPE)		
4-21 '75		5/12/75		—		
4-21 '75		5/12/75		一般公差		
4-21 '75		5/12/75		TOLERANCE		
4-21 '75		5/12/75		EXCEPT		
4-21 '75		5/12/75		AS NOTED		
4-21 '75		5/12/75		名称 (NAME)		
4-21 '75		5/12/75		"110" シリーズ ファストン リセプタクル (バラ状)		
4-21 '75		5/12/75		材料 (MATERIAL)		
4-21 '75		5/12/75		仕上 (FINISH)		
4-21 '75		5/12/75		平均電線断面積 (WIRE RANGE)		
4-21 '75		5/12/75		0.20~0.56 mm² (AWG 24-20)		
4-21 '75		5/12/75		被覆外径 (INSULATION DIA)		
4-21 '75		5/12/75		2.0~3.0 mm (080-120IN)		
4-21 '75		5/12/75		分類 CLASS		
4-21 '75		5/12/75		ファストン		
4-21 '75		5/12/75		型式 (TYPE)		
4-21 '75		5/12/75		—		
4-21 '75		5/12/75		一般公差		
4-21 '75		5/12/75		TOLERANCE		
4-21 '75		5/12/75		EXCEPT		
4-21 '75		5/12/75		AS NOTED		
4-21 '75		5/12/75		名称 (NAME)		
4-21 '75		5/12/75		"110" シリーズ ファストン リセプタクル (バラ状)		
4-21 '75		5/12/75		材料 (MATERIAL)		
4-21 '75		5/12/75		仕上 (FINISH)		
4-21 '75		5/12/75		平均電線断面積 (WIRE RANGE)		
4-21 '75		5/12/75		0.20~0.56 mm² (AWG 24-20)		
4-21 '75		5/12/75		被覆外径 (INSULATION DIA)		
4-21 '75		5/12/75		2.0~3.0 mm (080-120IN)		
4-21 '75		5/12/75		分類 CLASS		
4-21 '75		5/12/75		ファストン		
4-21 '75		5/12/75		型式 (TYPE)		
4-21 '75		5/12/75		—		
4-21 '75		5/12/75		一般公差		
4-21 '75		5/12/75		TOLERANCE		
4-21 '75		5/12/75		EXCEPT		
4-21 '75		5/12/75		AS NOTED		
4-21 '75		5/12/75		名称 (NAME)		
4-21 '75		5/12/75		"110" シリーズ ファストン リセプタクル (バラ状)		
4-21 '75		5/12/75		材料 (MATERIAL)		
4-21 '75		5/12/75		仕上 (FINISH)		
4-21 '75		5/12/75		平均電線断面積 (WIRE RANGE)		
4-21 '75		5/12/75		0.20~0.56 mm² (AWG 24-20)		
4-21 '75		5/12/75		被覆外径 (INSULATION DIA)		
4-21 '75		5/12/75		2.0~3.0 mm (080-120IN)		
4-21 '75		5/12/75		分類 CLASS		
4-21 '75		5/12/75		ファストン		
4-21 '75		5/12/75		型式 (TYPE)		
4-21 '75		5/12/75		—		
4-21 '75		5/12/75		一般公差		
4-21 '75		5/12/75		TOLERANCE		
4-21 '75		5/12/75		EXCEPT		
4-21 '75		5/12/75		AS NOTED		
4-21 '75		5/12/75		名称 (NAME)		
4-21 '75		5/12/75		"110" シリーズ ファストン リセプタクル (バラ状)		
4-21 '75		5/12/75		材料 (MATERIAL)		
4-21 '75		5/12/75		仕上 (FINISH)		
4-21 '75		5/12/75		平均電線断面積 (WIRE RANGE)		
4-21 '75		5/12/75		0.20~0.56 mm² (AWG 24-20)		
4-21 '75		5/12/75		被覆外径 (INSULATION DIA)		
4-21 '75		5/12/75		2.0~3.0 mm (080-120IN)		
4-21 '75		5/12/75		分類 CLASS		
4-21 '75		5/12/75		ファストン		
4-21 '75		5/12/75		型式 (TYPE)		
4-21 '75		5/12/75		—		
4-21 '75		5/12/75		一般公差		
4-21 '75		5/12/75		TOLERANCE		
4-21 '75		5/12/75		EXCEPT		
4-21 '75		5/12/75		AS NOTED		
4-21 '75		5/12/75		名称 (NAME)		
4-21 '75		5/12/75		"110" シリーズ ファストン リセプタクル (バラ状)		
4-21 '75		5/12/75		材料 (MATERIAL)		
4-21 '75		5/12/75		仕上 (FINISH)		
4-21 '75		5/12/75		平均電線断面積 (WIRE RANGE)		
4-21 '75		5/12/75		0.20~0.56 mm² (AWG 24-20)		
4-21 '75		5/12/75		被覆外径 (INSULATION DIA)		
4-21 '75		5/12/75		2.0~3.0 mm (080-120IN)		
4-21 '75		5/12/75		分類 CLASS		
4-21 '75		5/12/75		ファストン		
4-21 '75		5/12/75		型式 (TYPE)		
4-21 '75		5/12/75		—		
4-21 '75		5/12/75		一般公差		
4-21 '75		5/12/75		TOLERANCE		
4-21 '75		5/12/75		EXCEPT		
4-21 '75		5/12/75		AS NOTED		
4-21 '75		5/12/75		名称 (NAME)		
4-21 '75		5/12/75		"110" シリーズ ファストン リセプタクル (バラ状)		
4-21 '75		5/12/75		材料 (MATERIAL)		
4-21 '75		5/12/75		仕上 (FINISH)		
4-21 '75		5/12/75		平均電線断面積 (WIRE RANGE)		
4-21 '75		5/12/75		0.20~0.56 mm² (AWG 24-20)		
4-21 '75		5/12/75		被覆外径 (INSULATION DIA)		
4-21 '75		5/12/75		2.0~3.0 mm (080-120IN)		
4-21 '75		5/12/75		分類 CLASS		
4-21 '75		5/12/75		ファストン		
4-21 '75		5/12/75		型式 (TYPE)		
4-21 '75		5/12/75		—		
4-21 '75		5/12/75		一般公差		
4-21 '75		5/12/75		TOLERANCE		
4-21 '75		5/12/75		EXCEPT		
4-21 '75		5/12/75		AS NOTED		
4-21 '75		5/12/75		名称 (NAME)		
4-21 '75		5/12/75		"110" シリーズ ファストン リセプタクル (バラ状)		
4-21 '75		5/12/75		材料 (MATERIAL)		
4-21 '75		5/12/75		仕上 (FINISH)		
4-21 '75		5/12/75		平均電線断面積 (WIRE RANGE)		
4-21 '75		5/12/75		0.20~0.56 mm² (AWG 24-20)		
4-21 '75		5/12/75		被覆外径 (INSULATION DIA)		
4-21 '75		5/12/75		2.0~3.0 mm (080-120IN)		
4-21 '75		5/12/75		分類 CLASS		
4-21 '75		5/12/75		ファストン		
4-21 '75		5/12/75		型式 (TYPE)		
4-21 '75		5/12/75		—		
4-21 '75		5/12/75		一般公差		
4-21 '75		5/12/75		TOLERANCE		
4-21 '75		5/12/75		EXCEPT		
4-21 '75		5/12/75		AS NOTED		
4-21 '75		5/12/75		名称 (NAME)		
4-21 '75		5/12/75		"110" シリーズ ファストン リセプタクル (バラ状)		
4-21 '75		5/12/75		材料 (MATERIAL)		
4-21 '75		5/12/75		仕上 (FINISH)		
4-21 '75		5/12/75		平均電線断面積 (WIRE RANGE)		
4-21 '75		5/12/75		0.20~0.56 mm² (AWG 24-20)		
4-21 '75		5/12/75		被覆外径 (INSULATION DIA)		
4-21 '75		5/12/75		2.0~3.0 mm (080-120IN)		
4-21 '75		5/12/75		分類 CLASS		
4-21 '75		5/12/75		ファストン		
4-21 '75		5/12/75		型式 (TYPE)		
4-21 '75		5/12/75		—		
4-21 '75		5/12/75		一般公差		
4-21 '75		5/12/75		TOLERANCE		
4-21 '75		5/12/75		EXCEPT		
4-21 '75		5/12/75		AS NOTED		
4-21 '75		5/12/75		名称 (NAME)		
4-21 '75		5/12/75		"110" シリーズ ファストン リセプタクル (バラ状)		
4-21 '75		5/12/75		材料 (MATERIAL)		
4-21 '75		5/12/75		仕上 (FINISH)		
4-21 '75		5/12/75		平均電線断面積 (WIRE RANGE)		
4-21 '75		5/12/75		0.20~0.56 mm² (AWG 24-20)		
4-21 '75		5/12/75		被覆外径 (INSULATION DIA)		
4-21 '75		5/12/75		2.0~3.0 mm (080-120IN)		
4-21 '75		5/12/75		分類 CLASS		
4-21 '75		5/12/75		ファストン		
4-21 '75		5/12/75		型式 (TYPE)		
4-21 '75		5/12/75		—		
4-21 '75		5/12/75		一般公差		
4-21 '75		5/12/75		TOLERANCE		
4-21 '75		5/12/75		EXCEPT		
4-21 '75		5/12/75		AS NOTED		
4-21 '75		5/12/75		名称 (NAME)		
4-21 '75		5/12/75		"110" シリーズ ファストン リセプタクル (バラ状)		
4-21 '75		5/12/75		材料 (MATERIAL)		
4-21 '75		5/12/75		仕上 (FINISH)		
4-21 '75		5/12/75		平均電線断面積 (WIRE RANGE)		
4-21 '75		5/12/75		0.20~0.56 mm² (AWG 24-20)		
4-21 '75		5/12/75		被覆外径 (INSULATION DIA)		
4-21 '75		5/12/75		2.0~3.0 mm (080-120IN)		
4-21 '75		5/12/75		分類 CLASS		
4-21 '75		5/12/75		ファストン		
4-21 '75		5/12/75		型式 (TYPE)		
4-21 '75		5/12/75		—		
4-21 '75		5/12/75		一般公差		
4-21 '75		5/12/75		TOLERANCE		
4-21 '75		5/12/75		EXCEPT		
4-21 '75		5/12/75		AS NOTED		
4-21 '75		5/12/75		名称 (NAME)		
4-21 '75		5/12/75		"110" シリーズ ファストン リセプタクル (バラ状)		
4-21 '75		5/12/75		材料 (MATERIAL)		
4-21 '75		5/12/75		仕上 (FINISH)		
4-21 '75		5/12/75		平均電線断面積 (WIRE RANGE)		
4-21 '75		5/12/75		0.20~0.56 mm² (AWG 24-20)		
4-21 '75		5/12/75		被覆外径 (INSULATION DIA)		
4-21 '75		5/12/75		2.0~3.0 mm (080-120IN)		
4-21 '75		5/12/75		分類 CLASS		
4-21 '75		5/12/75		ファストン		
4-21 '75		5/12/75		型式 (TYPE)		
4-21 '75		5/12/75		—		
4-21 '75		5/12/75		一般公差		
4-21 '75		5/12/75		TOLERANCE		
4-21 '75		5/12/75		EXCEPT		
4-21 '75		5/12/75		AS NOTED		
4-21 '75		5/12/75		名称 (NAME)		
4-21 '75		5/12/75		"110" シリーズ ファストン リセプタクル (バラ状)		
4-21 '75		5/12/75		材料 (MATERIAL)		
4-21 '75		5/12/75		仕上 (FINISH)		
4-21 '						

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[170048-6](#)