



LOC	DIST	REVISIONS					
		P	LTR	DESCRIPTION	DATE	DWN	APVD
E	B		BA1	REVISED PER ECO-11-005150	28MAR2011	RK	HMR




1 PACKAGING: SUPPLIED TAPED AND REELED ON 13" REELS IN QUANTITIES OF 1500 PIECES

2 FOR FURTHER INFORMATION SEE DATA SHEET FOR 3615 SERIES-HIGH CURRENT INDUCTOR SMD

RECOMMENDED LAND PATTERN



RoHS Compliant



2008


RELEASED FOR PUBLICATION

ALL RIGHTS RESERVED.

THIS DRAWING IS UNPUBLISHED.

BY -

© COPYRIGHT 2008

DIMENSIONS:		DWN	13-NOV-08	MATERIAL		FINISH		
mm		SUBHASH.M		-		-		
TOLERANCES UNLESS OTHERWISE SPECIFIED:		CHK	13-NOV-08	TE Connectivity				
		PRAKASH.S						
		APVD	13-NOV-08					
		STEPHEN.P						
0 PLC ±0.2		PRODUCT SPEC		NAME				
1 PLC ±0.1		-						
2 PLC ±-		APPLICATION SPEC		HIGH CURRENT INDUCTOR SMD SERIES 3615				
3 PLC ±-								
4 PLC ±-		-		SIZE		CAGE CODE	DRAWING NO	RESTRICTED TO
ANGLES ±5°		WEIGHT 0.7g max.		A 4		00779	©- 1624097	-
CUSTOMER DRAWING				SCALE		5:1	SHEET 1 OF 1	REV BA1
								

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[3615A221K](#)