

4

3

2

1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION .19
 © COPYRIGHT 19 BY AMP INCORPORATED. ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS						
J	-	P	LTR	DESCRIPTION	ECN	DATE	DWN	APVD
		0		作成 RELEASED	FJ00-0158-98	30 JAN 98	ES	

NOTE,

- 1 APPLICABLE P.C. BOARD THICKNESS: 1.6mm
- 2 RECOMMENDED MOUNTING SCREW: 4mm DIA, 6mm LENGTH
TAPPING SCREW SPECIFIED IN JIS B1115, B1122
(TIGHTENING TORQUE: 4kgcm MAX)
- 3 THE MATING PLUG HSG P/N; 353112, 1123632

注:

- 1 通用プリント基板厚: 1.6mm
- 2 推奨取付ネジ: JIS B1115, B1122 タッピンネジ, ナベ 2種
呼び径 4, 長さ 6mm (締付トルク 4kgcm以下)
- 3 嵌合相手型番; 353112, 1123632

推奨プリント基板取付け寸法 (公差 ±0.1)
 (MOUNTING DIMENSIONS FOR P.C. BOARD; TOLERANCE ±0.1)
 ピッチ公差は累積しないこと (NON ACCUMULATE PITCH TOLERANCE)

緑 (GREEN)	1123630-4
色 (COLOR)	型番 (P/N)

THIS DRAWING IS A CONTROLLED DOCUMENT FOR AMP INCORPORATED. IT IS SUBJECT TO CHANGE AND THE CONTROLLING ENGINEERING ORGANIZATION SHOULD BE CONTACTED FOR THE LATEST REVISION.		OWN CHK E. Sasaki 30 JAN 98	AMP 日本エー・エム・ピー株式会社 Kawasaki, Japan	
DIMENSIONS: 単位 純 mm	TOLERANCES UNLESS OTHERWISE SPECIFIED	APVD 2. H. Sasaki	NAME .04011 SRS MULTI-LOCK CONN. MK-II 48Pos. CAP ASSY	RESTRICTED TO ---
MATERIAL HOUSING : PBT ハウジング : PBT CONTACT : BRASS コンタクト : 黄銅	FINISH 社上 PRE-TIN 錫めつき済	PRODUCT SPEC 108-5452	SIZE A2	DRAWING NO C-1123630
		APPLICATION SPEC 取付適用規格	CAGE CODE 00779	
WEIGHT 16.8g		CUSTOMER DRAWING		SCALE 2-1
				SHEET 1 OF 1 REV 0

AMP 1471-9 REV 10/93

参考図面

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[1123630-4](#)